

Lead to  
Marion Co

Report of Viewers. Field Notes and Plat of Survey of a County Road from 1/2 mile  
stake on W. side of Sec 35 Sp 1 N. R 26 E. ending near Pettysville.  
Road No 224

Report of Viewers.

To the Hon County Court. Umatilla County. Oregon.

We the undersigned viewers appointed on County Road No 224 beg to  
report that we met with Jno C. Arnold, Surveyor at the time and place appointed  
and after qualifying as directed by law. we took to our road Edward Lyons and Eugene  
Garrett who were qualified as chain bearer & being unable to procure further  
aid Edward Lyon was qualified as marker and we proceeded to view out survey and  
locate said Road No 224. we find the route to be quite good, and the road very much  
needed, and would therefore recommend that said road be declared a County Road by  
your Hon Body as by law directed.

Witness our hands this 18<sup>th</sup> day of August A.D. 1884

Thos M. Godley } Viewers  
C. M. Long }

Field Notes of the Survey of County Road No 224.

Having with a mason Theodilili found, by experiment the variation to be N. 22° E. I set  
sawed fir post 4x4x42 inches marked R on West face, in mound 45 links N.E. from 1/4 S.  
cor. bet. Secs 34 & 35 T 1 N. R 26 E. and with this variation N. 22° E. I run West 40.00 chs center  
Sec 35. about 10 ch. S of Tho Godley's Res. 80.00 chs 3/4 S. cor. bet Sec's 33 & 34. set 1 mile post  
45 links N. of R.C. (road center) 79.70 1/4 S. cor. bet. Sec's 32 & 33. set 2 mile post  
45 links N. of R.C. 36.50 set A.S. (angle stake) 45 lks. N. of R. C. angled N. 69° W.  
40.20 furrow on N & S. line through center Sec 32 set A.S. 45 lks. N. of R.C. and angled  
South 80.00 set 3 mile post 45 lks. west of R.C. in field 1.61 1/4 S. cor. on S. bndry. of  
Sec 32 - Base line. At this point I consumed about 3/4 day running random lines  
in search of cor. S. of base line and finding that these corners made a jog of about 63.89  
chs West. I run via 22° E. West 66.50 1/4 S. cor. on N. bndry of Sec. 5 T 1 S. R 26 E. set  
A.S. 45 lks. N. of R.C. and angled South 80.00 set 4 mile post 45 lks West of R.C.  
67.50 1/4 S. cor. bet. Secs 5 & 8. T 1 S. R 26 E. set A.S. 45 lks. N. W. and angled West  
80.00 set 5 m. post 45 lks. N. of R.C. 80.00 set 6 m. post 45 lks N. of R.C. 26.00  
Gov. cor for Secs. 1, 6, 7 & 12 on Sp line bet. ranges 25 & 26 E. 65.40 1/4 Sec. cor bet. Sec's  
14 & 12 T 1 S. R 25 E. set A.S. 45 lks. West and angled South 80.00 set 7 m. post 45 lks. west  
of R.C. 29.00 Ravine - Course N. E. & S. W. - set A.S. & angled S 9° 00' E. 38.50 across  
ravine - set A.S. and angled S 6° 15' W. 57.50 back to N & S line through center Sec 12.  
set A.S. near square dug pit 45 lks. West of R.C. and angled - via 22° E. South 64.00  
Rock cor. 1/4 S. bet Sec's 12 & 13 - near ravine. S of traveled road. set A.S. 45 lks. N. W.  
and angled West 80.00 set 8 mile post 45 lks. N. of R.C. 24.00 Gov. Cor. for Secs 11, 12, 13  
& 14, 36.00 set A.S. about 40 ft N. E. and angled across ravine. North 39.50 set A.S.