

met at the initial point of survey viz the S.W. corner of section 24 Township 5 north of Range 34 E W M this 1st day of October 1900 and after being duly sworn together with C.E. Macomber, Surveyor Wm Cooper Marker, Thomas Myers and James Myers Chairman proceeded to view locate and survey said road 517 and find the Route as located and surveyed to be practicable and would be useful to the public generally

Cass Cannon
William Piper
Gas Gerba

Field notes of Road 517 Beginning at a Stone monument set for the S.W. corner of section 24 Tp. 5 N. Range 34 E W M. 20-ft x 8-in post 3 1/2 ft long, 1 1/2 inches in ground, marked R 517, raised mound, and dug pits as required thence East on south boundary line of said section 24

Station	course	Dist.	Angle L	Ang R.	Remarks.
12 + 93	E	1293	91° 11'		to SE Cor of SW 4 of SW 24
52 + 80	N 1° 15' W	3987			Set 1 1/2" Post Mound & Pits.
55 + 53	N 30° 32' E	546'		4° 47'	
60 + 99	N 32° 07' E	523		28° 35'	
66 + 25	N 14° 55' E	55'	17° 12'		
67 + 10	N 53° 25' E	200		38° 33'	
69 + 10		100		53° 21'	
70 + 10		140		11° 51'	
71 + 50		100		14° 55'	
72 + 50		100	115'		
73 + 50		100		2° 54'	
74 + 50		100	129° 15'		
75 + 50		1067	5° 39'		
86 + 17		177		11° 18'	
87 + 94		200		15° 01'	
89 + 94		200		11° 34'	
91 + 94		166		39° 55'	
93 + 60		215		79° 05'	
96 + 78		548	74° 13'		
101 + 76		267		1° 19'	
103 + 93		2012		0° 54'	
105 + 60					Set 2 1/2" P. Mound & Pits
124 + 05		175	21° 00'		
125 + 83		445		19° 27'	
130 + 28		1860		8° 28'	
145 + 88		1135	2° 11'		

by the
locate
do
E W M.
together
Thomas
ceded to
and find
able and
generally

W Corner of
h. North
and built
line of
35 East W M
corner
East from
this in the
ments
or
Notes of

by the
Road