

July 23, 1901.

Survey made at request of C. Brown.
 Chairman - Lehal Brown
 Com. Brown
 Foreman - Bevell.

141
 200
 10

Beginning at a Stone mound
 Situated on a point of basal rock
 said mound being the Cor to Sec
 1, 2, 11, 12 to 1. N 31° 50' W. Thence

On true line to Sec 1 & 12. It 21° 55' E
 58 26 Set Stone 14x10x6 for Section Corner Sec
 1 & 12 on range line Thence

On Random line between Sec 6 & 7 in
 to 1. N. 32° E.

58 11 Intersect N 23° E line 86 feet N of Cor to
 Sec 5, 6, 7, 8. which is marked by
 an old wagon skin. I run thence
 on true line to establish Cor of Sec 2
 of the S W 1/4 of Sec 6.

59 60 Set old wagon skin for said corner
 I then return to S W cor of Sec 6 on
 Range line and run

Course	Degrees Minutes	Chains	Links	
North				On random line to Sec 186.
				5314 Subtrust Township line 34' E of Sec to Sec 186.
				I return to Co of Sec 67 on Range line and run on true line
North 0° 0' 21" W				on true line to Sec 146.
				1828 Set Stake for 1/4 Sec Cor Thence back on line parallel to South line of Section
				1851 Set Stake for Cor to and center of 3/4 of Sec 6. To P. N. R. 32 E.
				G. E. Macomber County Surveyor.