

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


T 1N, R 34E., W.M.

Corner Code No. R-11

Note: Monument marked as shown below

History of original corner establishment:

This corner was originally established by J.P. Currin and J.E. Moland, under Special Contract Dated May 4, 1887. The original notes state that at the corner a 10 x 8 x 6 in. basalt stone was set 7 in. in the ground, with a mound of stone over it. The stone was marked "1/4" on the north face.



Corner No.
Compass Declination: 18.0°

Description of corner evidence found:

Found a 13 X 7 X 5 inch basalt stone, with the top broke off and the "4" spalled off the stone but with horizontal cross line dividing the "1" and "4" clearly visible. This stone was setting upright and was surrounded with a mound of smaller stones. Bits of old rusted wire were found in the mound, and the remains of an old east by west fence line runs through the corner point. This corner stone was recovered after computing approximate corner point based on surrounding corners and surveying into the area.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position of the found corner stone, set a 2 1/2" brass cap on a 1 1/4" by 30" galv. iron pipe, 24" in the ground and surrounded with a mound of earth and stone. Buried the corner stone on the north side of the new monument. Set steel fence post west of corner and attached "Witness Corner" sign.

From the remonumented corner point:

A 8" hawthorne bears N 40° W, 64.3 feet, scribed 1/4 S 21 BT.
No other bearing trees are available so I established reference monuments as follows:

- A 1 1/2" alum. cap on a 5/8" by 30" iron pin bears N 43° E, 33.5 feet.
- A 1 1/2" yellow plastic cap on a 5/8" by 30" iron pin bears S 52° E, 34.3 feet.
- A 1 1/2" yellow plastic cap on a 5/8" by 30" iron pin bears S 43 1/2° W, 30.3 feet.

The 1 1/2" yellow plastic caps are marked "W.R. Wells, PLS 1106".

The 1 1/2" alum. cap is marked "RM", with an arrow pointing to the corner monument, the distance to the corner monument and "1106".

Set steel fence post near the reference monument with the 1 1/2" alum. cap and attached "Bearing Object" sign.

Attached "Bearing Object" signs to the reference monuments with the 1 1/2" yellow plastic caps with wire.

REGISTERED PROFESSIONAL LAND SURVEYOR

William R. Wells

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106

Office of the Survey Dept. County of Umatilla
State of OR, I hereby certify that the within instrument was filed in this office
for record on the 16th day of January, 1990

David A. Humphreys (COUNTY OFFICIAL) by Kathleen K. Ambrose (DEPUTY)

RECEIVED BY

Umatilla County Surveyor

Date 1-90

Rec'd by KA

No. 90-02-B