

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1882 by Herman D. Gradon, US Deputy Surveyor, under Contract Number 452. The Surveyor General's records state:


Set a basalt stone 14x9x7 ins. 9 ins. in the ground for 1/4 sec. cor. marked 1/4 on W-face and raised a mound of stone alongside.

The 1/4 section was monumented in 1998, by Kaiser/Griffin/ Seibold, Cadastral Surveyors under Bureau of Land Management Group No. 1844. The field notes state:

Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2-1/2 ins. diam., 16 ins. in the ground, to solid rock, and supported in a mound a stone, 3 ft. base, to top, with brass cap, from which:
A ponderosa pine, 46 ins. diam., bears S.1-1/4° W., 620 lks. dist., mkd. 1/4 S5 BT.

Deposited a magnet in a white plastic case at the base of the stainless steel post.



Description of corner evidence found:

Found 3-1/4" brass cap marked per the diagram on a 2-1/2" pipe, 0.6 feet above the ground in large rock mound.

Burnt and dead Ponderosa Pine bears S.01°W., 409.2 feet. (BLM Bearing Tree).

Description of monument and accessories I established to perpetuate the original location of this corner:

Chiseled "X" on South face 3 foot up from base of a 3' x 2' x 5.5' rock outcrop, bears N.37°W., 65.9 feet.

Chiseled "X" on Northwest face 1 foot up from base of a 1' x 1' x 1.5' rock, bearing S.67°E. 36.2 feet.

Set 5/8" x 24" rebar with 1-1/2" aluminum cap, bears N.54°E., 21.1 feet, stamped WSI/RM 21.1, 2535.

Set 5/8" x 24" rebar with 1-1/2" aluminum cap, bears N.72°W., 19.7 feet, stamped WSI/RM 19.7, 2535.

Reference monuments have an arrow pointing towards the corner. Appropriate signs have been attached to all bearing trees as required by this US Forest Service contract. 20° declination was used. Fieldwork was performed in May 2002.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Michael P. LeJeune

OREGON 11/06/02
JAN. 21, 1992
MICHAEL P. LE JEUNE
2535

EXPIRES 12/31/02

Prepared by: White Shield, Inc.
2515 W. Falls Ave.
Kennewick, WA 99336

Michael P. LeJeune,
Oregon PLS. 2535

Office ofCounty Surveyor....., County ofUmatilla.....,State of Oregon, I hereby certify that the within

instrument was filed in this office for record on theday of

David H. Allen
(County Official)

(Deputy)

RECEIVED BY

Umatilla County Surveyor

Date 11-02

Rec'd By JK

No. 02-273-B