


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**HISTORY OF ORIGINAL CORNER ESTABLISHMENT:**

THIS CORNER WAS ORIGINALLY ESTABLISHED BY GENERAL LAND OFFICE SURVEYORS WILLIAMS & PERSHIN UNDER CONTRACT NO. 154 DATED JUNE 6, 1871.

SURVEYOR GENERAL LAND OFFICE FIELD NOTES STATE:  
 "SET A STONE 17x10x8 ON N.W. HILLSIDE FOR CORNER TO SEC. 14, 15, 22, AND 23."

**DIAGRAM**



N-17

**DESCRIPTION OF CORNER EVIDENCE FOUND:**

FOUND A 17"X10"X8" STONE WITH 3 NOTCHES ON SOUTH FACE AND 2 ON EAST FACE, BURIED 1.0' UNDER ROCK JACK.

**DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

THIS CORNER WAS PERPERUATED BY SETTING A 5/8"X30" IRON ROD WITH 3-1/4" ALUMINUM CAP SET FLUSH AT THE LOCATION WHERE THE STONE WAS RECOVERED. THE ORIGINAL STONE WAS BURIED ALONGSIDE ON THE NORTH SIDE OF THE CAP.

THE CAP IS MARKED AS SHOWN BELOW.

THE REFERENCES SET FOR SAID CORNER ARE AS FOLLOWS:

- 1) A 5/8" X 30" IRON ROD WITH RED PLASTIC CAP STAMPED "ODOT CONTROL" BEARS N 58° E, 20.2 FEET.
- 2) A 5/8" X 30" IRON ROD WITH RED PLASTIC CAP STAMPED "ODOT CONTROL" BEARS S 22° E, 19.2 FEET.
- 3) A 5/8" X 30" IRON ROD WITH RED PLASTIC CAP STAMPED "ODOT CONTROL" BEARS S 21° W, 18.0 FEET.
- 4) A 5/8" X 30" IRON ROD WITH RED PLASTIC CAP STAMPED "ODOT CONTROL" BEARS N 32° W, 7.5 FEET.

BEARINGS WERE TAKEN WITH HANDHELD COMPASS AND WERE TAKEN TO THE NEAREST DEGREE.  
 DECLINATION = 14° E



WITNESSES:  
 BRENT REYNOLDS, LSIT  
 TRAVIS COFFELT

I HEREBY CERTIFY THAT THE ABOVE CORNER POSITION WAS RE-ESTABLISHED AS HEREON DESCRIBED ON MAY 3, 2021.

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR

*B. N. Elithorp*  
 OREGON  
 JAN 14, 2003  
 BRET N. ELITHORP  
 61348

EXPIRES: 12/31/2021



OREGON DEPARTMENT  
 OF TRANSPORTATION  
 REGION 5  
 SURVEY  
 UNIT

Section	VINSON CANYON QUARRY		
Highway	HEPPNER HIGHWAY		
County	UMATILLA	Scale	NTS
Purpose	BOUNDARY SURVEY	Date	MAY 27, 2021

21-064-B