


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A - 19
DIAGRAM

History of original corner establishment:

The original corner was established by George S. Pershin, deputy, (compassman) on October 24, 1871, under joint GLO contract No. 154, as follows:

Set a stone, 18" x 8" x 6", on north point of spur for 1/4 section corner to sections 2 and 35, T. 1 & 2 S., R. 30 E.



Original corner evidence recovered:

Found the original corner stone loosely set in a mound of stones. The corner stone is 17" x 8" x 5" and is faintly marked.

Monument and accessories established to perpetuate the original position of this corner:

In place of the original corner stone, I set a 1" x 30" flared, galvanized iron pipe 27" into the ground. A 2 1/2" brass cap attached to the top of the pipe is marked as shown in the diagram above. I bury the corner stone alongside the south side of the pipe and build a mound of stones around the pipe, from which:

- A 5/8" x 36" iron rod set 35" into the ground with a 3/4" brass washer, marked "PLS 1636 NE", attached at ground level, bears N43° 30' E, 143.6 feet.
 - A 5/8" x 36" iron rod set 35" into the ground with a 3/4" brass washer, marked "PLS 1636 SE", attached at ground level, bears S43° 30' E, 116.4 feet.
 - A 5/8" x 36" iron rod set 35" into the ground with a 3/4" brass washer, marked "PLS 1636 SW", attached at ground level, bears S42° W, 129.5 feet.
 - A 5/8" x 36" iron rod set 35" into the ground with a 3/4" brass washer, marked "PLS 1636 NW", attached at ground level, bears N28° W, 161.2 feet.
- I nail a "witness post" sign to a wooden fence post at the corner.

I hereby certify this corner point was perpetuated as hereon described on January 30, 2002. Magnetic declination set in compass: 18° E.

Dennis L. Gaylord

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 14, 1978
DENNIS L. GAYLORD
1636

Renews June 30, 2003

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on: _____

RECEIVED BY
Umatilla County Surveyor
Date 2-02
Rec'd By KE
No. 02-29-R