

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Herman D. Gradon surveyed under contract No. 452, dated June 16, 1882

Set a post 3 ft. long 3 ins. square 24 ins. in the ground for 1/4 sec. cor. mkd. 1/4 S on W face from which:

A fir 6 ins. diam. bears N 30° E., 12 lks. dist., mkd. 1/4 S BT

A fir 12 ins. Diam. bears N 70° W, 15 lks dist., mkd. 1/4 S BT



P-9

Description of corner evidence found:

None

Description of monument and accessories established to perpetuate the original location of this corner

Set 2 1/2 " brass cap on 2" iron pipe, 31 " long, 6 " above ground with 6' steel fence post 3' North and signs 54-4 and 54-2 attached, and the BTs established:

10" larch bears S. 47° 30' W., 14.9 ft. dist., mkd. 1/4 S 20 BT.
10" fir bears S. 53° 30' E., 8.8 ft. dist., mkd. 1/4 S 21 BT.

Corner marked:

T 1 S R 36 E
1/4
S 20 | S 21
RPE 2808
1976



Office of Surveyor County of Umatilla
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 26 day of August, 1976.
..... by
(COUNTY OFFICIAL) (DEPUTY)

Q-12