

OREGON CORNER RESTORATION FORM

COUNTY: Umatilla. DATE: 04/22/17.

CORNER DESIGNATION: N-3, The South one-quarter corner of Section 18, Township 2 North, Range 28 East, W.M..

PREVIOUS RENEWALS/SURVEYS ETC: Corner originally established by David P. Thompson Contract No. 83 dated July 22, 1859. Notes state: Set post for 1/4 Sec. corner in mound of earth & as per instructions. The corner point was reestablished by John Kimbrell, Deputy County Surveyor, in Survey No. 357, recorded at Record of Private Survey Book 2, Page 216, in December, 1912. Kimbrell reports setting a marked, square post 18" in the ground for the corner point.

MONUMENT AND ACCESSORIES FOUND: A partly obliterated old East-West fence line.

MONUMENT MARKING DETAIL:

T2N R28E
S18
1/4 -----
S19
2017
PLS 1106

MONUMENT SET: Reestablished corner point at intersection of proportional departure with the existing East-West fence line projections. At the reestablished corner point, set a 1 1/4" by 30" galv. iron pipe with 2 3/8" brass cap 27" in the ground and surrounded with a mound of earth, Cap is marked as shown in "Monument Marking Detail". There is a 4+ cubic foot granite stone located N 16° E, 10.5' from the corner monument.

New accessories:

- A 5/8" by 24" rebar with 1 1/4" red plastic cap bears N 52° E, 40.3 feet.
- A 5/8" by 30" rebar with 1 1/4" red plastic cap bears S 85° E, 29.8 feet.
- A 5/8" by 30" rebar with 1 1/4" red plastic cap bears N 85° W, 19.5 feet.
- A 5/8" by 24" rebar with 1 1/4" red plastic cap bears N 18° W, 36.3 feet.

Red plastic caps are marked "ORPLS 1106 WAPLS 17372". Set steel fence post 1 1/2 feet South of corner with "witness" sign wired to it. Wired "bearing object" signs to each rebar accessory.


LOCATION AND COMMENTS: Corner falls in an old fence line projection with fences East and West. There is a field road about 50 feet North of corner.

FIRM: Wells Surveying
P.O. Box 1696
Pendleton, OR 97801


COMPASS DECLINATION: 18° East

\2N28N3

Surveyor's Seal



William R. Wells



renews 6-30-18

17-065-C