

ARTIFIED RECORD OF LAND CORNER MONUMENTATION

T 2N, R 32E., W.M.

Corner Code No. N-15


Note: Monument marked as shown below

History of original corner establishment:

Most recent approved GLO record, by Currin and Noland, under Special Contract dated May 4, 1877 states:

"Old 1/4 Sec. cor. standing, redug pits 18x18x12 ins. E. & W. from stone 5 1/2 ft. dist. and raised a mound of Earth 1 1/2 ft. high 3 1/2 ft. base over it".

This corner was re-monumented or re-established by unknown methods during the Grecian Heights Subdivision. The corner is the initial Point of the Grecian Heights Subdivision, County Record Survey No. 1-102-B.



Corner No. Compass Declination: 18.0°

Description of corner evidence found:

Found a 2 1/2" brass cap on galv. iron pipe with a Survey Marker sign attached to railroad tie fence corner.

Description of monument and accessories I established to perpetuate the original location of this corner:

Maintained monument by surrounding with a small mound of stone. Referenced the existing monument with the following accessories:

- A 5/8" by 30" iron pin bears N 0 1/2° W - 13.96'.
- A 5/8" by 30" iron pin bears N 37° E - 17.19'.
- A 5/8" by 30" iron pin bears N 71 1/2° E - 19.96'.
- A 5/8" by 30" iron pin bears S 88° E - 16.79'.

All pins are capped with a yellow plastic cap marked "W.R. WELLS, PLS 1106", with steel fence posts set approx. 1' from each pin and Bearing Object signs attached to each post.

REGISTERED PROFESSIONAL LAND SURVEYOR

William R. Wells

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by ..... (COUNTY OFFICIAL) (DEPUTY)

RECEIVED BY Umatilla County Surveyor Date 8-9-72 Rec'd By KE No. 92-92-C