

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T 2N , R 32E. , W.M.

Corner Code No. P-25

Note: Monument marked as shown below :


History of original corner establishment:

Corner was originally established by David P. Thompson, under Contract No. 106, dated August 16, 1864. Set 1/4 section corner in mound of earth with charred stake, pits, trench and etc., as per instructions.

The corner was reset by Zenas F. Moody, under Contract No. 145, dated April 23, 1871. Set post and made mound of earth for the corner.

The corner was found by Jas. P. Currin and Jas. Noland, under Special Contract, dated May 4, 1887. Nothing was reset although the stone was gone.

The corner was reestablished by L.E. Wilkes, BLD Cadastral Surveyor, in 1917. Set an iron post, 3 feet long, 2 inches in diameter, 24 inches in the ground for the witness corner to the corner. The Witness Corner was set 45 1/2 links West of the corner point.



Corner No.
Compass Declination: 18.0°

Description of corner evidence found:

No evidence found of the corner.
Wilkes' witness corner monument has been destroyed.
Re-established corner by single proportionate measurement between the position for the West 1/4 of Section 19, T2N., R33E., and the location of the S 1/16th corner of Section 19, T2N., R33E., W.M.
Wilkes record was used for proportioning.

Description of monument and accessories established to perpetuate the original location of this corner:

At a position determined by survey:
Set a 2 1/2" brass cap on a 1 1/4" x 24" galv. iron pipe, 36 inches in the ground. Corner falls 6.5 feet East of the West edge of Powerline Road.
Set steel fence post 10.2 feet West of the monument with Witness corner sign.

New Bearing Objects:
A brass washer on powerpole No. 12-5 bears S 07° W - 139.0 feet. (1 foot above ground).
A 5/8" x 30" iron pin bears S 50° W - 29.5 feet. (Flush with the ground).
A 5/8" x 30" iron pin bears N 57 1/2° W - 26.7 feet. (Flush with the ground).
A brass washer on NE corner of substation chain link fence bears N 56° W - 83.7 feet. (1 foot above the ground).

All iron pins are capped with a 1 1/2" yellow plastic cap marked " WR WELLS, PLS 1106". Bearing Object signs are wired to each iron pin.
The brass washers are stamped "PLS 1106", and a Bearing Object sign is attached above each brass washer.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

Expires 12/31/94

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)