


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

E - 5  
DIAGRAM

**History of original corner establishment:**

The original corner was established by George S. Pershin on September 11, 1878, under GLO contract No. 293, as follows:

Set a stone, 16" x 10" x 8", for corner to sections 5, 6, 7 and 8. Dug pits and drove a willow stake as per instructions.



**Original corner evidence recovered:**

Found the original corner stone solidly set 9" into the ground. The original corner stone is 15" x 10" x 10" and is plainly marked with five notches on the east edge and one notch on the north edge. The stake and pits of record are gone.

**Monument and accessories established to perpetuate the original position of this corner:**

In place of the corner stone, I set a 1" x 30" flared, galvanized iron pipe 25" into the ground. I bury the corner stone along the north side of the pipe and build a mound of stones around the pipe. A 2 1/2" brass cap attached to the top of the pipe is marked as shown in the diagram above, from which:

- A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 S5", attached at ground level, bears N36° E, 121.6 feet.
- A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 S8", attached at ground level, bears S56° 30' E, 127.5 feet.
- A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 S7", attached at ground level, bears S49° W, 125.4 feet.
- A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 S6", attached at ground level, bears N63° W, 105.5 feet.

I hereby certify the above corner point was perpetuated as hereon described on February 9, 2004. Magnetic declination set in compass: 17° E.  
NAD '83 UTM Zone 11 position: 5031226N, 333769E (plus or minus two meters).



Renews June 30, 2005

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on:

RECEIVED BY  
Umatilla County Surveyor  
Date 2-04  
Rec'd By KK  
No. 04-35-R