

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

V - 13
DIAGRAM

History of original corner establishment:

The original corner was established by George S. Pershin on September 5, 1878, under GLO contract No. 293, as follows:

Set a stone, 20" x 10" x 8", on a rocky point for corner to sections 27, 28, 33 and 34. Raise a mound of stones around stake in lieu of pits, which cannot be dug.

T2S R30E
S28|S27
S33|S34
PLS 1636
2002

Original corner evidence recovered:

Found the original corner stone loosely set in a mound of stones. The corner stone is 19" x 7" x 6" and is plainly marked with three notches on one (east) edge and five notches on another (north) edge. The stake of record is gone.

Monument and accessories established to perpetuate the original position of this corner:

In place of the original corner stone, I set a 1" x 18" flared, galvanized iron pipe 10" into the ground to bedrock. A 2 1/2" brass cap attached to the iron pipe is marked as shown in the diagram above. I place the corner stone horizontally along the south side of the pipe and build a mound of stones around the corner stone and pipe, from which:

A 5/8" x 24" iron rod set 22" into the ground with a 3/4" brass washer, marked "PLS 1636 27", attached at ground level, bears N73° 30' E, 177.8 feet.

A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 34", attached at ground level, bears S49° 30' E, 104.6 feet.

A 5/8" x 24" iron rod set 19" into the ground with a 3/4" brass washer, marked "PLS 1636 33", attached at ground level, bears S73° W, 59.8 feet. I build a small mound of stones around this iron rod.

A 5/8" x 24" iron rod set 12" into the ground with a 3/4" brass washer, marked "PLS 1636 28", attached at ground level, bears N60° W, 63.8 feet. I build a mound of stones around this iron rod. The two references to the east are east of a gully.

I hereby certify the above corner point was perpetuated as hereon described on February 5, 2002. Magnetic declination set in compass: 16° E.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Dennis L. Gaylord
OREGON
JULY 14, 1978
DENNIS L. GAYLORD
1636

Renews June 30, 2003

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on:

RECEIVED BY
Umatilla County Surveyor
Date 2-02
Rec'd by KK
No. 02-37-R