


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

X - 25
DIAGRAM

History of original corner establishment:

The original corner was established by David P. Thompson on October 5, 1864, under GLO contract No. 106, as follows:

Set stone 24" x 6" x 6" for 1/4 section corner on top of a hill on a west slope.



Corner evidence recovered:

Found the original corner stone solidly set but tilted to the west. The corner stone is in a small mound of stones, is 24" x 9" x 5" and is very plainly marked "1/4" on the west face.

Monument and accessories established to perpetuate the original position of this corner:

In place of the original corner stone, I set a 1" x 30" iron pipe 12" into the ground to bedrock. I place a "Bearing Object" sign in the bottom of the hole as a memorial. I bury the corner stone along the northwest side of the pipe and build a mound of stones around the pipe to the cap. A 2 1/2" brass cap attached to the pipe is marked as shown in the diagram above, from which:

- A 5/8" x 36" iron rod set 35" into the ground with a 3/4" brass washer, marked "PLS 1636 NE", attached at ground level bears N47°E, 122.6 feet.
- A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 SE", attached at ground level bears S32°30'E, 59.2 feet.
- A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 SW", attached at ground level bears S20°W, 58.1 feet.
- A 5/8" x 36" iron rod set 35" into the ground with a 3/4" brass washer, marked "PLS 1636 NW", attached at ground level bears N13°W, 117.6 feet.

I hereby certify the above corner point was perpetuated as hereon described on September 15, 1998. Magnetic declination: 18° E.



Renews June 30, 1999

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on December 31, 1998, 1998

RECEIVED BY
Umatilla County Surveyor
Date 12-98
Rec'd By KK
No. 98-248-R

x4