

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

X - 17
DIAGRAM

History of original corner establishment:

The original corner was established by John C. Arnold on September 30, 1891, under GLO contract No. 551, as follows:

T2S R32E
1/4
S34+S35
PLS 1636
1999

Set a basalt stone, 18" x 10" x 4", 8" into the ground, marked "1/4" on west face, in a mound of stones.

Corner evidence recovered:


Found the original corner stone solidly set in a mound of stones. The corner stone is 22" x 17" x 5" and is plainly marked "1/4" on the west face.

Monument and accessories established to perpetuate the original location of this corner:

In place of the corner stone, I set a 2" x 30" iron pipe 13" into the ground to bed rock. A 2 1/2" brass cap attached is marked as shown in the diagram above. I bury the corner stone to the northeast of the pipe and build a mound of stones around the pipe to the cap, from which:

A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 NE", attached at ground level, bears N72°E, 57.4 feet.
A 5/8" x 24" iron rod set 17" into the ground with a 3/4" brass washer, marked "PLS 1636 SE", attached at ground level, bears S33°E, 87.2 feet.
A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 SW", attached at ground level, bears S62°W, 112.7 feet.
A 5/8" x 24" iron rod set 17" into the ground with a 3/4" brass washer, marked "PLS 1636 NW", attached at ground level, bears N58°W, 123.0 feet.
The reference rods to the southeast and northwest have a small mound of stones around them.

I hereby certify the above corner point was perpetuated as hereon described on October 2, 1999. Magnetic declination: 18°E.


Dennis L. Gaylord

Renews June 30, 2001

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on 12 Oct, 1999.

RECEIVED BY
Umatilla County Surveyor
Date 10-99
Rec'd By KK
No. 99-210-R