

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

X - 9  
DIAGRAM

History of original corner establishment:

The original corner was established by John C. Arnold on October 3, 1891, under GLO contract No. 551, as follows:

T2S R32E  
1/4  
S32|S33  
PLS 1636  
1998

Set a basalt stone, 10" x 8" x 7", 8" into the ground marked 1/4 on the west face in a mound of stones, from which:

- A 30" pine bears N80°W (no distance to this tree is shown in the original notes).
- A 24" fir bears east, 100 links (66.0 feet).

Corner evidence recovered:

There is a fence corner and a mound of stones at the corner point, with fences projecting north, west and south. The corner stone is gone. From the corner point:

- A 36" Western Larch with a healed blaze bears east, 66.0 feet. I open the blaze to visible scribes. This tree is nearly dead.
- A sawn and decayed Ponderosa Pine stump with scribes, "1/4 S", visible, bears N80°W, 20.7 feet.

Monument and accessories established to perpetuate the original position of this corner:

At the corner point as determined by reference to the record bearings to the two original witness trees, and the record distance to the witness tree east, I set a 1" x 30" iron pipe 20" into the ground. A 2 1/2" brass cap attached to the pipe is marked as shown in the diagram above. I build a mound of stones around the pipe to the cap, from which:

- A 12" Western Larch, scribed "1/4 S33 BT", bears N43°30'E, 33.7 feet.
- A 12" Ponderosa Pine, scribed "1/4 S33 BT", bears S66°E, 41.8 feet.
- A 19" Ponderosa Pine, scribed "1/4 S32 BT", bears S57°W, 60.6 feet.
- A 11" Ponderosa Pine, scribed "1/4 S32 BT", bears N28°30'W, 67.6 feet.

The four new bearing trees are scribed on double blazes, have a 3/4" brass washer, marked "PLS 1636", nailed flush the the scribed "B", and have a "Witness Post" sign nailed to the back of the tree. The four new bearing trees and the two original bearing trees have a "Bearing Object" sign nailed above the blazes.

I hereby certify the above corner point was perpetuated as hereon described on September 24, 1998. Magnetic declination: 18° E.



Renews June 30, 1999

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on December 31, 1998.

RECEIVED BY  
Umatilla County Surveyor  
Date 12-98  
Rec'd By AK  
No. 98-254-R