


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by David P. Thompson under GLO contract number 106, dated August 16, 1864. Surveyor General record states:

Set stone 20x15x10 in for corner to secs 1, 2, 34 & 35 from which;

A Pine 24 in diam bears N45°E 30 lks dist
A Pine 20 in diam bears N17°W 63 lks dist



No record of subsequent monumentation found in Umatilla County survey records.

Description of corner evidence found:

Found stone 19x12x10 inches with possible marks, loose on ground approximately 4 feet Northwesterly of corner position.

Found a 38 inch diameter Ponderosa Pine N45°E, 30 lks, live but sickly with scribes visible.

Found a 24 inch diameter Ponderosa Pine stump N17°W, 63 lks, with the bottom of the BT blaze visible.

Distance to the existing BTs are to the face of the blaze.

See survey dated September, 1988.

Description of monument and accessories I established to perpetuate the

original location of this corner: At record bearing and distance from the found original bearing trees, I set a 2 1/2" x 30" aluminum pipe with aluminum cap marked as shown, 30 inches in the ground, from which:

New BTs:

A 11 inch diameter Western Larch bears N30°E, 65.34 feet marked T2S R32E S36 BT
A 9 inch diameter Douglas Fir bears N60°W, 19.81 feet marked T2S R32E S35 BT

Painted a 6 inch red band around all BTs and attached bearing tree and land survey monument signs.
Set a steel fencepost approximately 5 feet East with land survey monument and property boundary signs attached.

Buried the original corner stone North and alongside of monument.

I hereby certify that the above corner point was perpetuated as hereon described on August 20, 1988.



REGISTERED
PROFESSIONAL
LAND SURVEYOR

Duane J. Griffith
OREGON
JULY 10, 1964
DUANE J. GRIFFITH
644

I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of Survey County of Umatilla

State of Ore. I hereby certify that the within instrument was filed in this office

for record on the 27th day of September, 1988

David N. Krummen by Kathleen K. Amberg
(COUNTY OFFICIAL) (DEPUTY)

RECEIVED BY

Form R6-7100-57 (9/71)

Umatilla County Surveyor

☆ U.S. GOVERNMENT PRINTING OFFICE - 1983-793-276

Date 9-88

Rec'd By KA

No. 88-62-C