

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z - 5
DIAGRAM

History of original corner establishment:

The original corner was established by David P. Thompson on October 9, 1864, under GLO contract No. 106, as follows:
Set stone 24" x 10" x 10" for corner to sections 31, 32, 5 and 6.



On May 27, 1882, George S. Pershin, under GLO contract No. 430, found a stone, about 18" x 12" x 7", on a south slope in a mound of stone. Pershin made this a corner of minimum control.

On October 4, 1891, John C. Arnold, under GLO contract No. 551, found a basalt stone, 18" x 12" x 8", marked with 5 notches on the east and 1 notch on the west edges, in a mound of stones on a south hillside.

Corner evidence recovered:

Found the original corner stone solidly set in a mound of stones. There are mounds of stones 3 feet to the southeast and 3 feet to the southwest of the corner stone. The corner stone is 24" x 17" x 12" and is plainly marked with 5 notches on the east edge and one notch on the west edge.

Monument and accessories established to perpetuate the original position of this corner:

In place of the corner stone, I set a 1" x 30" iron pipe 24" into the ground. A 2 1/2" brass cap attached to the pipe is marked as shown in the diagram above. I partially bury the corner stone along the west side of the pipe and build a mound of stones around the pipe to the cap. I do not disturb the original stone mound accessories. I establish additional accessories, as follows:

- A 5/8" x 24" iron rod set 22" into the ground with a 3/4" brass washer, marked "PLS 1636 S32", attached at ground level, bears N49°E, 87.5 feet.
 - A 5/8" x 36" iron rod set 34" into the ground with a 3/4" brass washer, marked "PLS 1636 SE", attached at ground level, bears S51°30'E, 87.6 feet.
 - A 5/8" x 36" iron rod set 34" into the ground with a 3/4" brass washer, marked "PLS 1636 SW", attached at ground level, bears S65°W, 87.1 feet.
 - A 5/8" x 36" iron rod set 34" into the ground with a 3/4" brass washer, marked "PLS 1636 S31", attached at ground level, bears N25°W, 116.1 feet.
- The easterly gate post in an east-west barbed wire fence bears S16°W, 159 feet. I place a "Witness Post" sign on this gate post.

I hereby certify the above corner point was perpetuated as hereon described on August 18, 1999. Magnetic declination: 18°E.



Renews June 30, 2001

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on _____, 1999.

RECEIVED BY
Umatilla County Surveyor
Date 9-99
Rec'd By KR
No. 99-145-R