


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

L - 13
DIAGRAM

History of original corner establishment:

The original corner was established on September 15, 1891, by John C. Arnold under his GLO contract No. 551, as follows:

Set a basalt stone, 16" x 8" x 8", 12" into the ground for 1/4 section corner, marked 1/4 on the west face. Dug pits, 18" x 18" x 12" deep, north and south, 5 1/2 feet distance, and raised a mound of earth, 2 feet high x 4 1/2 feet base, over the corner stone. Corner is on a north hillside.



Original corner evidence recovered:

Found the original corner stone solidly set with 5" protruding above the ground. A 2" x 34" iron water pipe is driven along the north edge of the stone. I find no record of establishment of this iron water pipe. The pits and mound of earth called in the original notes are no longer discernible. The corner stone is 19" x 10" x 10" and is plainly marked "1/4" on the west face.

Monument and accessories established to perpetuate the original position of this corner:

In the exact place occupied by the corner stone, I set a 1" x 30" galvanized, flared, iron pipe, 28" into the ground. I bury the corner stone along the east side of the pipe and bury the recovered 2" water pipe horizontally along the northwest side of the new pipe monument. A 2 1/2" brass cap attached to the new pipe monument is marked as shown in the diagram above, from which:

- A 5/8" x 36" iron rod, set 34" into the ground with a 3/4" brass washer, marked "PLS 1636 NE", attached at ground level, bears N35°E, 112.3 feet. This reference is north of a small draw.
 - A 28" Ponderosa Pine, scribed "1/4 S15 BT" on double blazes, bears S49° 45'E, 161.4 feet.
 - A 33" Ponderosa Pine, scribed "1/4 S16 BT" on double blazes, bears S78° 30'W, 252.5 feet.
- Both of these trees have a 3/4" brass washer, marked "PLS 1636", nailed flush to the scribed "B", and have a "Bearing Object" sign nailed above the blazes.
- A 5/8" x 36" iron rod, set 35" into the ground with a 3/4" brass washer, marked "PLS 1636 NW", attached at ground level, bears N42°W, 41.8 feet.

I hereby certify the above corner point was perpetuated as hereon described on January 9, 2001. Magnetic declination set in compass: 18°E. Witness: Jerry McKague.

Renews June 30, 2001

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on:

RECEIVED BY

Umatilla County Surveyor

Date 02-01

Rec'd by AK

By 01-21-R