


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. N-11

History of original corner establishment:

In 1882 under GLO Contract No. 451, Rufus S. Moore set a post 3 ft. long, 3 in. square, 24" in ground for 1/4 Sec. 16 and 21 marked 1/4 S on N face.
From Which:

- A Pine 9" in dia. bears N29°W 24 lks. marked 1/4 S BT.
- A Fir 14" in dia. bears S10°W 8 lks. marked 1/4 S BT.



Description of corner evidence found:

Found: A 28" Doug. Fir axed open to face of blaze with no visible scribing. Tree is dead.

A 12" dia. Lodgepole Pine with open blaze and visible scribing "1/4 S BT" is uprooted and rolled out of position.

At record bearing and distance from the Fir and the root hole of the Pine we found remains of the decayed post.

Description of monument and accessories established to perpetuate the original location of this corner:

At this established point we set 2 1/2"x30" galvanized pipe with brass cap stamped:

Set pipe 25" in ground.

From which:

The original Fir BT still standing bears S10°W 5.25 ft.

New BT's:

- A White Fir 10" dia. bears N29°E 42.0 ft., marked 1/4 S16 BT.
- A Tamarack 17" dia. bears S74°E 45.1 ft., marked 1/4 S 21 BT.


Painted blazes and attached signs per Standard Specifications for Cadastral Surveys, USFS Region 6, Oct., 1979.

Corner falls on a steep W slope about 200 ft. above the bottom of a draw in partly open timber and about 1 ft. north of an east-west fence.

Compass Declination: 18 1/2° E

I hereby certify the above described corner monument and/or accessories was established as described on July 29, 1982.

Witnesses: G. Wagoner
R. Scott



Office of..... Surveyor..... County of..... Umatilla
 State of..... Oregon..... I hereby certify that the within instrument was filed in this office
 for record on the 30 day of September 1982
 David Krumbein by Betty Shatto
 (COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

MM

RECEIVED BY
 Umatilla County Surveyor
 Date 9-82
 Rec'd By BLS
 No. 82-104-R

☆ GPO 799-509