

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

N-3

History of original corner establishment:

This corner was originally established by Rufus S. Moore under G.L.O. contract no. 451 dated June 12, 1882. He set a wood post 3' long and 3" square 24" in the ground.
From which:


- A Pine, 3" dia., N46°W, 24 lks.
- A Pine, 3" dia., S70°E, 53 lks.

L.E. Wilkes, U.S. Surveyor, did not find this corner during his resurvey in 1917. At proportionate distance he set a 1" by 3" iron pipe with a brass cap marked:

- From which:
- A Lodgepole, 6" dia., S30°W, 6 lks.
- A Lodgepole, 6" dia., N60°E, 7 lks.

Description of corner evidence found:

None.



$\frac{1}{4}$ $\frac{S18}{S19}$
1917

Description of monument and accessories established to perpetuate the original location of this corner:

At proportionate distance set a 2½"x30" alum pipe with a 3" alum. cap containing a magnet and marked:

From which:

- A D. Fir, 10" Dia., N17½°W, 24.2 ft. marked: $\frac{1}{4}$ S18 BT
- A D. Fir, 11" dia., S73°E, 22.4 ft. marked: $\frac{1}{4}$ S19 BT

T2S R35E

$\frac{1}{4}$ $\frac{S18}{S19}$

PLS 1832
1984

BTs have blaze and a 6" stripe painted red, a BT tag, an "Attention" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with an "Attention" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18°E.

September 5, 1984.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S. Munro
OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832

Office of Surveyor County of Umatilla
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 10 day of October 1984
David H. Krumbain by _____
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

84-134-R GPO-788-276

84-001-B

N-3