


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

14 /

History of original corner establishment:

This corner was originally established by Rufus S. Moore under G.L.O. contract no. 451 dated June 12, 1882. He set a wood post 3' long and 3" square 24" in the ground, from which:

- A Pine, 8" dia., N24°W, 9 lks.
- A Spruce, 4" dia., S33°W, 3 lks.



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

At proportionate distance set a 2 1/2"x30" alum. pipe with a 3" alum. cap containing a magnet and marked:

From which:

- A W. Fir, 6" dia., N44°E, 12.5 ft. marked: 1/4 S17 BT
- A Spruce, 7" dia., S52 1/2°W, 50.2 ft. marked: 1/4 S20 BT

T2S R35E

1/4 S17
S20

PLS 1832
1984

BTs have blaze and a 6" stripe painted red, a BT tag, an "Attention" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with an "Attention" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 17 1/2°E.

September 8, 1984.



Office of Supervisor County of Umatilla
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 10 day of October, 1984
David H. Keumeein by Fayette S. Munro
 (COUNTY OFFICIAL) (DEPUTY)

N-7

84-100-B 84-135-R