

OREGON CORNER RESTORATION FORM

COUNTY: Umatilla. DATE: 04/20/23.

CORNER DESIGNATION: G-9, the East Quarter Corner of Section 8, Township 3 North, Range 28 East, W.M.

PREVIOUS RENEWALS/SURVEYS ETC: Corner was originally established by N.H. Gates under Contract No. 84, dated July 22, 1859. Gates set a post in earth mound. Survey No. 240, found in Record of Private Survey Books, reestablished the corner at mid-point between Section corners North and South and set a stone for the corner. The corner area was surveyed through in Survey No. 84-56-B but no corner was established or monumented.

MONUMENT AND ACCESSORIES FOUND: None. I reestablished the corner point by single proportion measure between the Northeast and Southeast corners of Section 8.

MONUMENT MARKING DETAIL:

T3N R28E
1/4
S8 | S9
2023
PLS 54657

NEW MONUMENT SET:

At the position determined by survey set a 2 1/2" brass cap on 1 1/4" by 30" galvanized iron pipe 30" in the ground. At a depth of 18" below ground, I encountered a 16"X8"X8" stone, broken in half and lying flat. I did not identify any chisel marks on the stone pieces. I placed the stone pieces East of the new corner monument. The corner area has been farmed in the past, but is not currently farmed. The brass cap is marked as shown in Monument Marking Detail. Set a wood fence post 1' North of monument and attached witness sign. The corner falls in field berm with faint remains of an old North-South fence line. The corner point is in an unimproved portion of County Road No. 1333.

New accessories:

A Silver Deep-1 magnet buried 22" below ground line bears N 38°39'22" E, 30.03'. Buried bearing object sign with the Deep-1 magnet.

A Pink Deep-1 magnet buried 22" below ground line bears S 58°59'43" E, 38.01'. Buried bearing object sign with the Deep-1 magnet.

A 5/8"X24" rebar with blue plastic cap marked "Wells Surveying 54657PLS" bears S 00°24'19" E, 34.51'. Wired bearing object sign to the rebar. Found old post and wire remains near this rebar.

A Orange Deep-1 magnet buried 22" below ground line bears N 57°21'41" W, 31.78'. Buried bearing object sign with the Deep-1 magnet.

Courses to corner accessories are State Plane Grid bearings and distances.

LOCATION AND COMMENTS: The corner falls in an unfarmed area that has been farmed in the past, in old remains of a North-South field berm with faint remains of a North-South fence line.

OREGON STATE PLANE COORDINATE, North Zone NAD 83(91), International Feet Units:

N: 763647.35
E: 8500303.40

FIRM: Wells Surveying
P.O. Box 1696
Pendleton, OR 97801

Surveyor's Seal

\3N28G-9



24-004-C

RENEWS: 6/30/24