

**OREGON CORNER RESTORATION FORM**

Section 29  
County Umatilla

Township 3N  
Date: 02/17/10

Range 29E

Corner Designation: 3N29R9

Corner common to sections 20,21,28 and 29, T3NR29E.

- Condition Report Only
- Not Found
- Remonumented
- Unrecorded
- Surveyed In
- Referenced Out


**Previous Renewals / Surveys, etc.**

Originally Surveyed by N.H. Gates in 1859. He set a post in a mound of earth. Staebler set a 1 x 30" iron pipe w/ 2 1/2" B.C. on survey I-158-B.

**Monuments and Accessories Found: (Condition and Source)**

None.

**Diagram**



**Sketch**

● Orange Magnet

● Silver Magnet

○ 2 1/2" B.C.  
18" Deep

● Blue Magnet

● Pink Magnet

NAD 83/91  
OREGON STATE PLANE NORTH  
INTERNATIONAL FEET

N750805.01  
E8532907.12

LAT - 45° 43' 07.55737466" N  
LON - 119° 12' 17.14203346" W

**Monument (s) Set (Procedures and Description)**

A 2 1/2" Brass cap on 1"x30" Galvanized Iron Pipe 18" deep, near an irrigation pivot. Stamped as shown above.

Reset corner from referenced ties to Staebler's survey.

**References Set:** "Deep One" magnets by Bernsten.

An Orange magnet 20" deep lies N 58°00' W, 17.02'.

A Blue magnet 20" deep lies S32 °20' W, 13.18'.

A Silver magnet 20" deep lies N 44°00' E, 18.26'.

A Pink magnet 20" deep lies S 64°30' E, 16.61'.

**Location and Comments**

The corner is .5 miles West of the intersection of Hwy 320 and Snow Road, North of the House in a field.

**Compass Declination**

17° E

**Surveyors Seal**

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Robert D. English*  
OREGON  
JANUARY 11, 2005  
ROBERT DOUGLAS ENGLISH  
43406LS

**RECEIVED BY:**

Date: 3-10  
Rec'd By: KK  
No. 10-388

**Firm / Agency**

Survey One, LLC.  
P.O. Box 382  
Pendleton, OR 97801  
(541) 276-2055

RENEWAL DATE: 12/31/11