

# OREGON CORNER RESTORATION FORM

COUNTY: Umatilla DATE: 5/5/15

CORNER DESIGNATION: The West One-Quarter Corner of Section 5, Township 3 North, Range 31 East, C-5.

PREVIOUS RENEWALS/SURVEYS ETC.: Corner originally established by D.S. Payne, under Contract No. 100, dated 8/1/1861, notes state: Set charred stake with mound trench and pits as per instrs. for 1/4 sec corner.

MONUMENT AND ACCESSORIES FOUND: None.

MONUMENT MARKING DETAIL:

T3N R31E  
1/4  
S6|S5  
2015  
PLS 54657

MONUMENT SET:

Held intersection of field berm extending South with old fence remains EastWest as best remaining evidence of original corner location and set a 2 3/8" brass cap on a 1 1/4" x 30" galvanized iron pipe, with top 20" below ground level stamped as shown in "Monument Marking Detail".

From which:

- A silver deep-1 magnet buried 20" in the ground bears North 44° East, 29.0 feet.
- A pink deep-1 magnet buried 20" in the ground, bears South 51° East, 31.7 feet.
- A blue deep-1 magnet buried 20" in the ground, bears South 39° West, 31.1 feet.
- An orange deep-1 magnet buried 20" in the ground, bears North 48° West, 33.4 feet.

Buried bearing object tags with magnets.

LOCATION AND COMMENTS: At intersection of field berm extending South with old fence remains East-West.

OREGON STATE PLANE COORDINATE, North Zone, NAD 83(91), International Feet:

N = 770569.01  
E = 8591447.66

FIRM: Wells Surveying  
P.O. Box 1696  
Pendleton, OR 97801

COMPASS DECLINATION: 18° East Surveyor's Seal

Witnesses: Jason Wells, PLS  
Dean Roy

/3N31C5



RENEWS: 6-30-16

15-052-C