

**OREGON CORNER RESTORATION FORM**

COUNTY: Umatilla DATE: 04/12/06

CORNER DESIGNATION: 3N31, R-25, The Southeast Corner of Section 24.

PREVIOUS RENEWALS/SURVEYS ETC.: Corner originally established by D.S. Payne, under Contract No. 100, dated August 1, 1861. Record states: Set charred stake with mound, trench and pits as per insts. for corner to Secs. 24 & 25, T. 3 N., R. 31 E. & Secs. 19 & 30, T. 3 N., R. 32 E. Hayes, in undated survey No. Q-521-C, calls for a unmarked stone found. Hayes survey indicates a 1 inch pipe was set for the corner.

MONUMENT AND ACCESSORIES FOUND: None. We did find bits of fence wire, below ground, when searching for this corner.

**MONUMENT MARKING DETAIL:**

T3N  
R31E R32E  
S24|S19  
S25|S30  
2006  
PLS 1106

**MONUMENT SET:**

Established corner position 3963.3 feet South of the recovered 1 inch iron pipe established for the North 1/16th corner common to Section 24 and 19, per Hayes Survey No. Q-521-C (undated). For alignment South of the 1 inch iron pipe, held the record calculated angle of 66°23'46" to the right, when occupying the 1 inch iron pipe and back sighting the recovered fence corner near the center 1/4 corner of Section 19, T3N., R32E., W.M. The stone and iron pipe reported on Survey No. Q-521-C was not recovered. We made an extensive search for the monuments reported for Section 19 on Survey No. Q-521-C and found only the 1 inch pipe for the N 1/16th corner common to Section 24 and 19, the old fence corner near the center 1/4 of Section 19 and an uprooted 1 inch pipe near the South 1/16th corner common to Section 13 and 18. At reestablished corner position, set a 2 3/8" brass cap on 1 1/4" x 30" galvanized iron pipe with top 15" below ground level. Monument marked as shown in monument marking detail.

**From which:**

A silver Deep-1 magnet buried 24" below ground level bears North 53 1/2° East, 37.0 feet.  
A blue Deep-1 magnet buried 24" below ground level bears South 43° East, 39.9 feet.  
A purple Deep-1 magnet buried 24" below ground level bears South 39° West, 32.1 feet.  
An orange Deep-1 magnet buried 24" below ground level bears North 29° West, 34.1 feet.  
Set steel fence post with witness sign attached 1 foot North of monument. Buried bearing object signs with all magnets.

LOCATION AND COMMENTS: Corner is located in a North-South field line in a farmed area. No other features nearby.

OREGON STATE PLANE COORDINATE, North Zone, NAD 83(91), International Feet:

N = 752068.17  
E = 8618141.93


FIRM: William R. Wells, PLS  
P.O. Box 1696  
Pendleton, OR 97801

COMPASS DECLINATION: 18° East

Surveyor's Seal

Witnesses: Jason Wells, LSIT

/3N31R25



*William R. Wells*  
OREGON  
JULY 22, 1977  
WILLIAM R. WELLS  
1106

renews 6-30-08 06-11-06