


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

N-19
T3N R36E

1/4 CORNER TO SECTIONS 14 & 23, T3N, R36E

History of original corner establishment:

ESTABLISHED BY G. S. PERSHIN UNDER HIS CONTRACT No. 305, DATED MAY 4, 1878. HIS NOTES READ AS FOLLOWS:
N89°35'W ON A TRUE LINE BETWEEN SEC. 14 AND 23.
38.50 RAVINE, COURSE SOUTH
39.61 SET STONE 20x12x4 ON EAST HILLSIDE FOR 1/4 SEC. COR.



Description of corner evidence found:

NO EVIDENCE FOUND.

Description of monument and accessories established to perpetuate the original location of this corner:

ON A STRAIGHT LINE BETWEEN SECTION CORNERS AND AT A POINT 1.11 CHAINS (73.3 FT.) WESTERLY OF A RAVINE AS CALLED FOR IN ORIGINAL G.L.O. NOTES, I SET A 2"x30" ALUMINUM PIPE WITH A 2 1/2" ALUMINUM CAP, STAMPED AS SHOWN, 26" IN GROUND.

FROM WHICH:

MY NEW B.T., A 22" P.R., SCRIBED "1/4 S23BT" BEARS S 1 3/4° W, 163.6 FT.

NO OTHER TREES WITHIN LIMITS IN SEC. 14.

T3N R36E
S 14
1/4 S 23
1986
LS 934

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Victor M. McInd

OREGON
JULY 17, 1970
VICTOR M. McIND
934

RECEIVED BY

Umatilla County Surveyor

Date 7-8-86

Rec'd By KA

No. 86-81-M

(86-37-B)

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL)

(DEPUTY)