


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

S.E. 1/4 Cor. Sec. 1, T3N R37E

History of original corner establishment:

No RECORD



D-24

Description of corner evidence found:

NONE.

Description of monument and accessories established to perpetuate the original location of this corner:

SET 2x30" ALUMINUM PIPE WITH 2 1/2" ALUMINUM CAP, MARKED AS SHOWN ABOVE, 24" IN GROUND, FROM WHICH:

A FIR, 9" DIAM., SCRIBED "SE 1/4 S1 BT" BEARS N 21 1/2° W, 7.9 FT.

A SPRUCE, 8" DIAM., SCRIBED "SE 1/4 S1 BT" BEARS S 66 1/4° W, 19.0 FT.

SET A STEEL POST 3' SOUTH OF CORNER WITH SIGN 54-4.

PRINTED A RED BAND AROUND BOTH BT'S, AND ATTACHED SIGN 54-3 ABOVE BLAZE AND SIGN 54-4 TO BACK OF TREES.

REGISTERED PROFESSIONAL LAND SURVEYOR

Victor M. McLeod

OREGON JULY 17, 1970 VICTOR M. McLIND 934

RECEIVED BY

Umatilla County Surveyor

Date 7-31-86

Rec'd By FA

No. 86-100-2

Office of SURVEYOR County of UMATILLA

State of OREGON, I hereby certify that the within instrument was filed in this office for record on the day of 1986

(COUNTY OFFICIAL) by (DEPUTY)