


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Corner originally established by John W. Kimbrell under GLO contract number 700, dated February 9, 1899. Surveyor General record states:

The closing corner is a basalt stone 20x12x7 ins 12 ins in the ground for closing cor of T3N R38E marked CC T3N R38E on E side with 6 grooves on N and E faces, from which;

A fir 28 ins diam bears N31°E, 175 lks dist marked CC T3N R38E S31 BT



No record of subsequent monumentation found in Umatilla County survey records.

**Description of corner evidence found:**

Found a stone 19x11x7 inches with chisel marks visible.

Found a 36 inch diameter Ponderosa Pine stump N31°E, 175 lks with scribes visible.

**Description of monument and accessories I established to perpetuate the**

**original location of this corner:** In place of the found original corner stone, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown, 20 inches in the ground, from which:

**New Bearing Trees and Bearing Object:**

- A 12 inch diameter Douglas Fir bears N3°E, 185.3 feet marked T3N R38E S31 CC BT
- A 16 inch diameter Douglas Fir bears S67°E, 218.0 feet marked T2N R38E S6 CC BT
- A 5/8"x30" iron pin with plastic cap marked BGA SURVEY MARKER bears West, 4.13 feet
- A 25 inch diameter Douglas Fir bears N75°E, 125.9 feet marked X BT
- Raised a mound of stone around monument, 4 ft. base to top of cap.
- Buried the original corner stone East and alongside of monument.
- Painted a 6 inch red band around all bearing trees and attached Bearing Tree and Land Survey Monument signs.

Set a steel fencepost approximately 5 feet East with Land Survey Monument sign attached.

I hereby certify that the above corner point was perpetuated as hereon described on August 13, 1991.



**REGISTERED PROFESSIONAL LAND SURVEYOR**

*Duane I. Griffith*  
OREGON  
JULY 10, 1964  
**DUANE I. GRIFFITH**  
644

I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

**RECEIVED BY**  
Umatilla County Surveyor  
Date 10-92  
Rec'd By KR  
No. 92-118-R