

USDA-FOREST SERVICE

Index File No. K-19

T 45 R. 30E

Merid. Willamette

CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)


R.D. Ukiah County Umatilla

N.F. Umatilla State Oregon

Tract or Survey No. \_\_\_\_\_ Cor. No. \_\_\_\_\_

CORNER DIAGRAM

T45 R30E



DESCRIBE CORNER MONUMENT FOUND

Corner not previously established.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

N/A

PHOTO IDENTIFICATION DATA

Photo No. \_\_\_\_\_

Filed At. \_\_\_\_\_

Object Ident. \_\_\_\_\_

Ident. By \_\_\_\_\_

*Signature*

PLANE COORDINATE POSITION DATA

State \_\_\_\_\_ Zone \_\_\_\_\_

X \_\_\_\_\_

Y \_\_\_\_\_

Estab. By \_\_\_\_\_

*Agency*

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

Corner is on flat ground in pine timber approx. 250 ft. North from a primitive road.

*Signature*

Title

Division

Headquarters

Date

7100-52-(3/68)

PLS 848

Mt. Vernon, OR

7/31/81

5

**CORNER RECORD (PERPETUATION)**

**MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT**

Set 3"x30" galv. iron pipe with 3" brass cap stamped as shown on the diagram, set 24 inches in the ground.

From which:

**ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE**

A pine 16 in. dia. bears N71°W, 29.5 ft. scribed CN 1/16 S 14 BT.  
A pine 14 in. dia. bears S 19°E, 69.3 ft. scribed CN 1/16 S 14 BT.  
Set steel post with warning and boundary signs 5 ft. West and 4 ft. East from corner. Nailed bearing tree signs and brass washers stamped PLS 848 to each tree. Painted red band around each tree.

Work Done By D. M. Ferguson Title Surveyor Date 7/31/81 State Registration No. OR PLS 848  
or Agency

Certified Copy Record Prepared? Yes  No  Filed At: Umatilla Co. Surv. Off. Date 10/81

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

**REMARKS**

Witnesses to above corner:

D. Mitchell Ferguson  
Mike Woodward

**OREGON  
JULY 12, 1968  
DOUGLAS M. FERGUSON  
848**