

Index File No. T-22
 T 45 R. 30E
 Merid. Willamette

CORNER RECORD (SEARCH)
 (Ref. FSM 7151.4)

Tract or Survey No. _____ Cor. No. _____

R.D. Ukiah County Umatilla
 N.F. Umatilla State Oregon

CORNER DIAGRAM



T45 R30E

W 1/16

C ——— C

S 25

1981

PLS 848

6

PHOTO IDENTIFICATION DATA

Photo No. _____
 Filed At. _____
 Object Ident. _____
 Ident. By _____
Signature

7

PLANE COORDINATE POSITION DATA

State _____ Zone _____
 X _____
 Y _____
 Estab. By _____
Agency

8

DESCRIBE CORNER MONUMENT FOUND

Corner not previously established.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

N/A

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

Corner in bottom of side draw approx.
 250 ft. SW from main draw bottom.
 A road follows main draw bottom.

Signature

Title PLS 848

Division _____

Headquarters Mt. Vernon, Or

Date 7/30/81

7100-52-(3.68)

5

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Set 3"x30" galv. iron pipe with 3" brass cap stamped as shown on the diagram. Set pipe 18 inches in the ground and raised a mound of stone around the pipe.



From which:

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A pine 8 inches dia. bears S13°E, 23.2 ft. scribed CW 1/16 S 25 BT.
A pine 8 inches dia. bears N54°E, 67.7 ft. scribed CW 1/16 S 25 BT.
Set steel posts with warning and boundary signs 5 ft. South and 5 ft. East from corner.
Nailed bearing tree signs and brass washers stamped PLS 848 to each tree.
Painted red band around each tree.

Work Done By D.M. Ferguson Title Surveyor Date 7/30/81 State Registration No. or Agency OR PLS 848

Certified Copy Record Prepared? Yes No Filed At: Umatilla Co. Surveyor Off. Date _____



REMARKS

Witnesses to above corner:

D. Mitchell Ferguson
Mike Woodward