


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1882 by George S. Pershin under General Land Office Contract No. 430.

Surveyor General Record States:

Set basalt stone 18 x 12 x 5 ins. for  $\frac{1}{4}$  cor. marked with  $\frac{1}{4}$  on North face.

A 28" Pine bears N 8 E, 72 lks.  
A 9" Pine bears S77 E, 50 lks.



2-19

No record of subsequent remonumentation was found in County Records.

Description of corner evidence found:  
Found original stone, call size, marked  $\frac{1}{4}$  in mound of stone, from which:

Original BTs


A 20" Pine, good condition, bears S64E 33.5 ft., blaze healed.  
A 35" Pine, good condition, bears N11E 48.8 ft., scribes visible.

Description of monument and accessories I established to perpetuate the original location of this corner

In position of stone, I set  $2\frac{1}{2}$ "x30" iron pipe with brass cap, marked as shown, 24" in ground.

I took no new BTs.

Buried stone North and along side pipe.  
Set steel fence post 5+ ft. East of corner.  
Used steel tape and magnetic compass with 20° E declination.  
Measured to face of blaze of original BTs.



Office of Surveyor County of Umatilla  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 13 day of April, 1974, at        o'clock        m., (signed)  
Ralph Thompson by         
 (COUNTY OFFICIAL) (DEPUTY)

F-109-R