

CORNER RECORD (PERPETUATION)

GPO-902-673

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Set 2½"x30" galvanized pipe with brass cap marked:
Set pipe 20" in the ground to bedrock and mound of stone around.

T4S R32E
NE 1/16 S17
OR PLS 1051
1977

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A pine 10" in dia. bears S43⁰E, 19.7 feet, scribed NE 1/16 S17 BT. A pine 10" in dia. bears N26⁰W, 36.5 feet, scribed NE 1/16 S17 BT. Placed 54-3 and 54-4 on BTs and brass washer stamped PLS 1051 on BT blazes. Painted blazes red and 6" red band around BTs. Placed 54-2 and 54-9 on fence post 4' West of corner. Placed 54-2 and 54-4 on fence post 5' north of corner.

Work Done By B.B. Barbour Title P.L.S. Date 11/4/77 State Registration No. OR PLS 1051
or Agency

Certified Cor. Record Prepared ? Yes No Filed At _____ Date _____

REMARKS

Witnesses to the above: D.L. Landers, S. Nelson

Index File No. _____ T. _____ R. _____ M. _____ Tract or Surv. No. _____ Cor. _____