


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. C-21

History of original corner establishment:

In 1881, under Glo Contract No. 410, George S. Pershin set a stone 18x10x8, from which a 9" Pine bears N18°W, 24 lks.; and a 15" Pine bears S44°E, 63 lks.



Description of corner evidence found:

Found original stone firmly set, undisturbed, with 1/4 on west face.

Found a 27" P. Pine bearing S42°E, 42.2 ft., with blaze healed.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2"x30" aluminum capped aluminum pipe rising 5", stamped:

Deposited original stone with "1/4" in north side of aluminum capped aluminum pipe in hole.

T4S R33E  
1/4  
S2 | S1  
RLS 1848  
1984

New BT's:

An 8" West. Larch bears S84°W, 66.8 ft. scribed 1/4 S2 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Set metal post 3 ft. north of corner.

Compass Declination: 19 1/2° E      Witness: D. Scott

From 2110, take 2110-320 northeasterly approx. 1.1 mi. Turn right on 2110-330 and right again in 1/4 mi. on 211--334 and go to the end of the road, which is in a big clearing on top of a hill. Corner is at the west end of the clearing 100 ft. into the woods.

I hereby certify the above described corner monument and/or accessories was established as described on May 30, 1984.



Office of Surveyor County of Umatilla  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 10<sup>th</sup> day of July, 1984  
David K. Kambouris by Betty Cochran  
 (COUNTY OFFICIAL) (DEPUTY)