


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-17

History of original corner establishment: Corner established in 1883 by F. W. Campbell under General Land Office Contract No. 468.



Surveyor General Record States:

Set post for cor. to Sect's. 2-3-10-11, From which:

- A 12" Tamarack bears N 61 E, 61 lks.
- A 24" Tamarack bears S 47 W, 29 lks.
- A 20" Tamarack bears N 40 W, 37 lks.
- A 12" Fir bears S 50 E, 10 lks.

No record of subsequent remonumentation was found in County Records.  
Description of corner evidence found:

Found original BTs as follows:

- A 8" Tamarack snag bears N29E, 40.0 ft., scribes visible.
- A 17" Fir snag bears S75E, 6.6 ft., blaze healed.
- A 30" Tamarack, good condition, bears S28W, 22.7 ft., scribes visible.
- A 32" Tamarack, good condition, bears N53W, 24.4 ft., scribes visible.


Description of monument and accessories I established to perpetuate the original location of this corner

At corner point, based on record distance to BTs, I set 2 1/2"x30" iron pipe with brass cap marked as shown, 24" in ground, from which:

New BTs

- A 13" Fir bears N41E, 67.0 ft. marked T5S R30E S2 BT.
- A 12" Fir bears S59E, 68.5 ft. marked T5S R30E S11 BT.

Nailed brass washer to BT blaze.  
Set steel fence post 5+ ft. South and 5+ East of corner.  
Corner is approximately 6 ft. South of small creek.  
Used steel tape and magnetic compass with 20° E declination.  
Measured to face of blaze of original BTs and center of new BTs.



Office of Surveyor County of Umatilla  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 13 day of Aug, 1974, at        o'clock        m., (signed)  
Ralph Thompson by        (DEPUTY)  
 (COUNTY OFFICIAL)

E-17

S-63-M