

USDA-FOREST SERVICE

Index

File No. 711

TSS

R30E

Merid. Willamette

CORNER RECORD (SEARCH)

Ref. FSM 7151.4

North Fork John Day

Umatilla

Tract or

Survey No

County Umatilla

State Oregon

Cor.

No.

x

1

1

Corner Diagram

SC

1 Describe corner monument found

T5S R30E

1 None

1/4 533

1

1988

1

PLS 852

1

1

1

x

1

x

Photo Identification Data

1 Describe bearing trees or other official accessories found

Photo No.

1 The remains of a 12" fir were found pushed up in a slash pile. It was not

filed at

1 possible to determine where this tree had been. A 9" White Fir was found dead

Object Ident.

1 and down. The location of this tree and the monument set by his crew in 1977

Ident. by

1 was discussed with PLS 933. We agreed that the corner should be re-established

Signature

1 based on new evidence found since his previous survey.

x

1

x

Plane Coordinate Position Data

1 Describe corner location relative to near-by features, also how to reach corner

State

Zone

1 From the junction of roads 5312 and 5320, follow road 5320 east 1.2 miles to

X

1 road 5320105. Follow road 5320105 south 0.5 miles to an east-west fence line.

Y

1 Follow this fence line east approximately 450' to the first of the only trees

Estab. by

1 left standing along the fence in the clearcut. This tree is one of the new

Agency

1 bearing trees for the corner which is located about 90' north of the

x

1

x

Signature

Title

Division

Headquarters

Date

7100.52

David L. Haroldock Land Surveyor

Pendleton, OR

June 1988

CORNER RECORD (PERPETUATION)

X

X

Monument: Describe new monument set, or work done to preserve existing monument

set by reposition -

Set 30" aluminum pipe 26" in the ground at a point on the First Standard Parallel which was half way between the SE and SW corners of section 33. Stamped the cap as shown in the diagram on the front of this form. Placed a collar of stone around the monument. Set a steel fence post 5' west of the monument and attached a Forest Service Land Survey Monument sign.

X

X

X

Accessories: Describe new BT's witness objects etc. established, or work done to preserve existing evidence

A 9" Douglas Fir bears N86°45'E, 78.8' scribed 1/4 S33 SO BT in a 30" blaze.

A 7" Douglas Fir bears S36°00'E, 72.1' scribed 1/4 S33 SO BT in a 30" blaze.

Nailed an aluminum washer stamped RLS 852 between the letters B and T on each tree. Made a band around each tree. Painted the blazes and the bands red. Attached a Forest Service Land Survey Monument and Bearing Tree sign to each tree.

X

X

Work done by David L. Haddock Title Land Surveyor Date Nov 1988
 Certified cor. record prepared? yes x no Filed at Pendleton, OR

State Registration No. 852
 or Agency
 Date ~~Dec 1988~~
 Jan 1989

X

X

REMARKS

X

X

Index File No. Z-11 T.5S. R.30E. M. Willamette Tract or Survey No Cor.

USDA-FOREST SERVICE

Index File No. 2-11


CORNER RECORD (SEARCH)
(Ref. FSM 7151.4)

Tract or Survey No. _____ Cor. No. _____

T. 5S. R. 30E. R.D. Ukiah County Umatilla
Merid. Willamette N.F. Umatilla State Oregon

CORNER DIAGRAM

T. 5S., R. 30E.



DESCRIBE CORNER MONUMENT FOUND

None.

Set brass cap

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

Old BT on ground. Location could not be found.

PHOTO IDENTIFICATION DATA

Photo No. _____
Filed At. _____
Object Ident. _____
Ident. By _____
Signature

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

From the intersection of U.S. Forest Road 419N and 537N, go East 2 miles to a fence, then west along fence 35 chns. to corner.

PLANE COORDINATE POSITION DATA

State _____ Zone _____
X _____
Y _____
Estab. By _____
Agency

Signature
David H. Klev

Title _____ Division OPLS Headquarters 933 Date 7-77 7100-52-(3/68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

T. 5S., R. 30
S.33Set 2½" x 30" iron pipe with brass cap.
Pipe is 27" in ground.SC
1977
PLS 933

Stamped:

9

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A 9" fir bears N. 76°49' W. 31.0 ft.
A 12" fir bears N. 63°58' E. 15.7 ft.Set steel post 4 ft. East of corner w/sign.
Painted red band around bearing tree w/sign.

10

Work Done By T. Hamby Title Party Chief Date 6/22/77 State Registration No. _____
or Agency _____Certified Cor. Record Prepared ? Yes No _____ Filed At: _____ Date _____ 11

REMARKS

12

Index File No. T. R. M. Tract or Surv. No. Cor. 13