


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1880 by Geo. S. Pershin, under Contract No. 361



Surveyor General Record States:

80.00 set basalt stone 15x12x4 on level for corner to Sec. 34 & 35

Pine 20 in. diam. brs. N. 36° E. 168 lks dist.

No tree in N.W. raised mound of stone three feet in diam. & 18 in. high around corner.

No record of subsequent remonumentation found in County Records.

Description of corner evidence found:

At the corner point: Found a stone 15x9x5 set in a mound of stone on level ground found no trace of Orig. BT. stone mkd with 2 grooves.

Record distance to closing corner between sections 1 & 2 (7.20 chains) checks out within a foot or so, therefore I accept the position of this corner.

Description of monument and accessories established to perpetuate the original location of this corner:

At the Standard corner to Secs. 34 & 35: Set a 2 1/2"x30" galvanized iron pipe 12" in the ground on solid rock in 4 ft. diam. mound of stone with brass cap marked as shown. Buried original stone East and alongside pipe, From which I scribe NEW BEARING TREES:

A pine 24 in. in diam. brs. N. 42° E. 119.7 ft. mkd T5S R30E S35 SC BT.

A pine 9 in. in diam. brs. N. 62° W. 193.9 ft. mkd T5S R30E S34 SC BT.

Nailed brass washer marked "OPLS 598" to the BT blaze of both trees. Set steel fence post 5 ft. West of corner. Used compass with 20° E. Variation and steel tape measuring to center of BTs. Barbed wire fence 15 ft. South of corner. Bears East & West.


REGISTERED PROFESSIONAL LAND SURVEYOR

Robert D. Baggett

OREGON JULY 12, 1903 ROBERT D. BAGETT 598

Sept 30, 1976

County Surveyor Umatilla Office of Oregon State of Oregon, I hereby certify that the within instrument was filed in this office for record on the day of 1976 by (COUNTY OFFICIAL) (DEPUTY)



2-17

J-107-R