


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by George S. Pershin under General Land Office Contract No. 410. Surveyor General Records state:
Set basalt stone 12 X 8 X 6 ins. for 1/4 sec. cor. No trees.
Raised mound of stone along side.



No record of subsequent remonumentation was found in county records.

Description of corner evidence found:

Found stone 12" X 8" X 6" marked 1/4.

(See map of Survey, dated December, 1975)

Description of monument and accessories established to perpetuate the original location of this corner


At corner position I set 2 1/2" X 30" iron pipe with brass cap marked as shown 28" in ground, from which:

A 12" Lodgepole Pine bears N 8° W, 268.6 ft. marked
T4S R33E 1/4 S34 BT.

A 14" Lodgepole Pine bears S 70° E, 409.0 ft. marked
T5S R33E 1/4 S3 BT.

Buried stone East and along side pipe.

Set steel fence post 5+ ft. East.



Brass Washer nailed to BT blazes.
Used steel tape and magnetic compass with 19°30' East declination.
Measured to center of all BTs.

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the day of.....
..... by
(COUNTY OFFICIAL) (DEPUTY)

2-15