


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. K-24

History of original corner establishment:

No Corner was originally set.



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner: At surveyed point set 2 1/2"X30" galvanized pipe with brass cap stamped: Set pipe 24" in ground with mound of stone to cap.

T5S R33E
NE 1/16 S13
1980
OR PLS 1294


Bearing Trees:

A White Fir 6" dia bears N22°W, 12.7 ft., scribed NE1/16 S13 BT.
A White Fir 6" dia bears S33°W, 20.7 ft., scribed NE1/16 S13 BT.

Attached 54-3 & 54-4 signs to both BTs. Attached brass washer stamped LS 1294 to foot blaze of both BTs. Painted blazes and 6" band around both BTs Red. Attached 54-2 & 54-4 signs to metal post 5 ft north of corner. Attached 54-2 & 54-9 signs to metal post 5 ft east of corner.

I hereby certify the above corner monument was established as herein described on July 9, 1980.

Witnesses: R. Orton
L. Huntsman
D. Allen



Office of..... County Surveyor..... County of..... Umatilla
State of..... Oregon....., I hereby certify that the within instrument was filed in this office for record on the..... day of..... December....., 19.80
..... David Rumbert..... by..... Betty Shotts.....
(COUNTY OFFICIAL) (DEPUTY)

R-187-B