

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

1882, George S. Pershin, U.S. Deputy Surveyor, while subdividing the township under G.L.O. Contract No. 430 established the corner as follows:  
Set Basalt Stone 16 X 10 X 8 ins 11 ins in ground on west slope for 1/4 Sec. cor. marked 1/4 on North face  
A Pine 20 in. dia. brs. N. 86° W. 33 lks dist marked 1/4 S.B.T.  
A Pine 18 in. dia. brs. S. 85° W. 24 lks dist marked 1/4 S.B.T.

1976, Duane I. Griffith, LS 644,  
Found 26" P. pine, NW BT scribes visible.  
No evidence of other BT found.  
At record bearing and distance from the NW BT set 2 1/2" X 30" iron pipe with brass cap 26" in ground from which:  
Original BT:  
A 26" P. Pine bears N 86° W, 21.8 ft. scribes visible.  
New BT's:  
A 10" P. Pine bears N 89° E, 31.5 ft. marked T5S R33E 1/4 S17 BT.  
A 10" P. Pine bears S 04° E, 29.6 ft. marked T5S R33E 1/4 S20 BT.

1984, David H. Krumbain, LS 933, while surveying sections 20 and 21 (CS# 84-155-B, revised 12/20/84: CS# 85-43-B) found the brass cap.


N-07  
240400  
T. 5 S., R. 33 E.  
1/4 corner of sections 17 & 20



Description of corner evidence found:

Found a 2 1/2" diameter iron pipe, with 2 1/2" diameter brass cap, projecting 10" out of the ground, marked as shown, from which:

13" Ponderosa Pine bears S 4 1/2° E, 29.6 feet, with scribing visible on almost completely healed double blaze.  
29" Ponderosa Pine bears N 87 1/2° W, 21.8 feet, with scribing visible on chopped open blaze.



Description of monument and accessories I established to perpetuate the original location of this corner:

New References:

11" Ponderosa Pine bears N 28 1/4° E, 65.7 feet, scribed "1/4 S17" "BT".  
17" Ponderosa Pine bears S 48° E, 47.3 feet, scribed "1/4 S20" "BT".

The new bearing trees are double blazed and have a 3/4" diameter brass washer stamped "RLS 2308" nailed to the lower blaze by the "BT" scribing.

DATUM: NAD83(1991) Oregon High Accuracy Reference Network  
STATE PLANE COORDINATES: Oregon North Zone in International Feet  
No. Latitude Longitude Northing(Y) Easting(X)  
240400 45°07'38.39285" N. 118°44'51.67167" W. 537420.253' 8654306.764'

Work Performed By: David A. Schlaich (RLS 2308)  
Equipment: Topcon GPT-6005C Total Station  
Magnetic Declination: 19 1/2' East  
Date: October 1, 2002

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*David A. Schlaich*

OREGON  
JULY 16, 1987  
DAVID A. SCHLAICH  
2308

RENEWAL DATE: 06/30/2004

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 20.....  
..... by.....  
(COUNTY OFFICIAL) (DEPUTY)