


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

George S. Pershin under G.L.O. Contract No. 430, dated Mar. 23, 1882, set a basalt stone 18"x 12"x 7", 12" in ground. Stone marked with 1 notch on south and 5 notches on east. From corner:  
Tamarack, 12" dia., N64°E, 15 lks..  
Tamarack, 10" dia., S82°E, 45 lks..  
Alder, 8" dia., S88°W, 43 lks..  
Tamarack, 12" dia., N17°W, 57 lks..



Continued on Page 2 of 2.

T5S R33E  
S30|S29  
S31|S32  
1977

**Description of corner evidence found:**

I found a 2 1/2" iron pipe with a 3 1/4" brass cap (BLM) marked as above. From the corner:  
W. Larch, 26" dia., N64°E, 13.4 ft.; with healed blaze.  
W. Fir, 16" dia., dead, N10°W, 32.3 ft.; scribing visible.  
W. Fir, 11" dia., dead, S49°E, 33.0 ft.; " "  
W. Fir, 27" dia., dead, S50°W, 52.1 ft.; " "

**Description of monument and accessories I established to perpetuate the original location of this corner:**

I marked new BTs:  
W. Fir, 20" dia., N28°W, 93.4 ft.; marked: T5S R33E S30 BT  
Spruce, 14" dia., S45 1/2°E, 40.3 ft.; marked: T5S R33E S32 BT  
5/8"x 30" iron pin (rebar) driven 26" in ground, S39°W, 25.7 ft.; with 1 1/2" yellow plastic cap marked: PLS 1832

BTs have blaze and a 6" band painted red, BT tags and "Land Survey Monument" signs. New BTs have, additionally, alum. "PLS 1832" washers nailed to the bottom of the blaze. There is a 6' steel fence post with a "Land Survey Monument" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 20°E.

June 12, 1991

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Fayette S. Munro*

OREGON  
JULY 13, 1978  
FAYETTE S. MUNRO  
1832

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

RECEIVED BY  
Umatilla County Surveyor  
Date 12-91  
Rec'd By SK  
No. 91-97-R

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

Craig L. Wanless, Cadastral Surveyor, under special instructions, Group No. 350, found stone per the record. He set a 2 1/2" x 28" iron post with brass cap marked:

From corner:

Larch, 25" dia., N64°E, 15 lks.; healed blaze.

Larch snag, 18" dia., S82°E, 45 lks.; scribing visible.


Root hole N17°W, 57 lks.; down tree, scribed alongside.

He marked new BTs:

Grand Fir, 10" dia., S49°E, 50 lks.

Grand Fir, 25" dia., S50°W, 79 lks.

Grand Fir, 13" dia., N10°W, 49 lks.



T5S R33E  
S30 | S29  
S31 | S32  
1977

**Description of corner evidence found:**

Description of monument and accessories I established to perpetuate the original location of this corner:



Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

RECEIVED BY  
Umatilla County Surveyor  
Date 12-91  
Rec'd By JK  
No. 91-97-R