



LAND CORNER RECORD

GRANTOR/SURVEYOR/PUBLIC OFFICER: This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY: William R. Wells Land Surveying
 ADDRESS: P.O. Box 1696
 357 NE Hwy. 11
 Pendleton, OR 97801

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR
William R. Wells
 OREGON
 JULY 22, 1977
 WILLIAM R. WELLS
 1106
renews 6-30-02
7/31/01
 SEAL/SIGNATURE/DATE

GRANTEE: PUBLIC

LEGAL: TWP: 6N RGE: 32E CORNER CODE:A-15

ADDITIONAL IDENTIFIER: (BLM designation, street or plat names, block, lot, etc.)
 NORTH 1/4 CORNER SECTION 3.

COUNTY: Walla Walla

OREGON PLANE COORDINATES: N: 868590.54 E: 8635061.27, (inf ORN 83/91)

ORDER:

CORNER INFORMATION: Discuss the history, evidence found, and perpetuation of the corner. Diagram the references; provide the date of work; and, if applicable, a reference to a map of record and/or the field book/page no. Use the back, if needed.

1. HISTORY:

Corner originally established by Daniel G. Major under Contract No. 72 dated May 25th, 1863. Record states: Set a post for quar. Sec. corner, made mound with trench and pits and drove charred stake.

Line was retraced and corner visited by Edwin Richardson, under Special Instructions dated February 22, 1867.

2. EVIDENCE FOUND: Found a 12" x 9" x 7" stone with no visible marks, in mound of stone. These are the only stones in the area.

3. PERPETUATION INFORMATION

At position of found stone, set a 2 1/4" brass cap on a 1" x 30" galvanized iron pipe with cap 1" above ground level. Cap marked as shown:

T7N R32E
 S34
 1/4 -----
 S3
 T6N
 2001
 PLS 17372

Buried found stone 1.0 West of monument with top of stone above ground. From new monument:
 A 5/8" x 30" iron rebar with a yellow plastic cap stamped "OR PLS 1106, WA PLS 17372", set flush with the ground bears S 52° E, 40.6 feet.
 A 5/8" x 30" iron rod with a yellow plastic cap stamped "OR PLS 1106, WA PLS 17372", set flush with the ground, bears N 05° W, 37.7 feet.

Set steel fence post about 1 foot South of corner monument. Compass declination 18° East.

This form is in compliance with the intent of RCW 65.04.045 and prescribed by the Public Land Survey Office, Department of Natural Resources - 1/97.
 16N32A15ORN

RECEIVED BY
 Umatilla County Surveyor
 Date 09-01
 Rec'd By KE
 No. 01-111-B