

OREGON CORNER RESTORATION FORM

COUNTY: Umatilla DATE: 06/18/01

CORNER DESIGNATION: P-21

PREVIOUS RENEWALS/SURVEYS ETC.: Corner originally established by Nicholas O. Walden, U.S. Dept. Surv., under Contract No. 209, dated July 6, 1874. Record states: Set a basalt stone, 12 x 8 x 6, 7 ins. in ground, for Cor. to Land.

MONUMENT AND ACCESSORIES FOUND: A mound of stone, 3 1/2 foot in diameter, with 2 stones of near record size but no visible markings.

MONUMENT MARKING DETAIL:

T6N R32E
1/4
S23 | S24
2001
PLS 1106

MONUMENT SET: At center of found stone mound, set a 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum pipe with top 4" above mound, marked as shown in "Monument Marking Detail".
From which:

- A silver deep-1 magnet, buried 14" in ground, bears N 44° E, 29.0 feet.
- A purple deep-1 magnet, buried 14" in ground, bears S 84° E, 40.1 feet.
- A blue deep-1 magnet, buried 14" in ground, bears S 31° W, 26.5 feet.
- An orange deep-1 magnet, buried 14" in ground, bears N 70° W, 32.2 feet.

Buried bearing object tags along with all deep-1 magnets. Set steel fence posts 2.0 feet South of corner "witness" sign attached.

LOCATION AND COMMENTS: Corner is located at Westerly side of a rocky ridge—area to the North has been previously farmed. There is a fence running NE-SW about 300' South of corner.

OREGON STATE PLANE CO-ORDINATES, OREGON NORTH, NAD 83(91): *fti*
N: 850545.61
E: 8642651.73

FIRM: William R. Wells, PLS
P.O. Box 1696
Pendleton, OR 97801

COMPASS DECLINATION: 18° East

Witnesses: Jason Wells, LSIT
Mark Hammersla

\6N32P21

Surveyor's Seal

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Will. R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

renews 6-30-02

RECEIVED BY
Umatilla County Surveyor
Date 09-01
Rec'd By KE
No. 01-139-C