

**OREGON CORNER RESTORATION FORM**

COUNTY: Umatilla DATE: 06/20/01

CORNER DESIGNATION: T-9

PREVIOUS RENEWALS/SURVEYS ETC.: Corner originally established by Nicholas O. Walden, U.S. Dept. Surv., under Contract No. 209, dated July 6, 1874. Record states: Drove charred stake & raised mound of earth, with pits, etc., as per instructions, for 1/4 Sec. Cor.

MONUMENT AND ACCESSORIES FOUND: Accepted intersection of old East-West fence line and field line extending South as best remaining evidence of the original corner location.

MONUMENT MARKING DETAIL:

T6N R32E  
1/4  
S29 | S28  
2001  
PLS 1106

MONUMENT SET: At intersection of fence and field lines, set a 2 1/2" aluminum cap on a 2 1/2" x 30" aluminum pipe with top 3" above ground level, marked as shown in "Monument Marking Detail".

From which:

- A silver deep-1 magnet, buried 18" below ground level, bears N 47 1/2° E, 40.2 feet.
- A purple deep-1 magnet, buried 18" in below ground level, bears S 51° E, 39.3 feet.
- A brass washer stamped "PLS 1106", 1.0 feet above ground level, in Pacific Power and Light pole #299500, bears S 59° W, 6.4 feet.
- An orange deep-1 magnet, buried 18" in the ground, bears N 35° W, 33.7 feet.
- Buried bearing object tags along with the deep-1 magnets.
- Attached bearing object tag and "witness" sign to power pole near corner monument.

LOCATION AND COMMENTS: Corner is located at a point where an East/West fence and field line intersects a field line from the South.

OREGON STATE PLANE CO-ORDINATES, OREGON NORTH, NAD 83(91): ~~421~~  
N: 844772.40  
E: 8626603.51

FIRM: William R. Wells, PLS  
P.O. Box 1696  
Pendleton, OR 97801

COMPASS DECLINATION: 18° East

Witnesses: Jason Wells, LSIT  
Mark Hammersla  
16N32T9

Surveyor's Seal

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR

*Will. R. Wells*

OREGON  
 JULY 22, 1977  
 WILLIAM R. WELLS  
 1106

*renews 6-30-02*

**RECEIVED BY**  
 Umatilla County Surveyor  
 Date 9-01  
 Rec'd By [Signature]  
 No. 01-139-C