


History of original corner establishment:

Frank W. Campbell under G.L.O. contract number 468, dated April 12, 1883, set a basalt stone 24"X 10"X 6", 18" in the ground, from which:

- A Fir, 24" dia., N70°E, 165 lks.
- A Pine, 24" dia., S44°E, 100 lks.
- A Pine, 30" dia., S49°W, 142 lks.
- A Pine, 30" dia., N53°W, 9 lks.



U.S. Cadastral Surveyors under special instructions Group Numbers 350 and 643 set the corner from original BTs:

- A Pine, 30" dia., S44°E, 95 lks, with a healed blaze.
- A Pine stump, 30" dia., N53°W, 9 lks., with no marks visible.

(Continued on Page 2 of 2.)

Description of corner evidence found:

I found a 2 1/2" iron pipe with a brass cap marked: in a stone mound. From the corner:

T6S R32E
S29 S28
S32 S33
1968

- A Ponderosa Pine, 12" dia., N66°W, 116.8 ft., with a healed blaze.
- A Douglas Fir, 12" dia., N67°E, 59.4 ft., with scribing visible.
- A Ponderosa Pine, 34" dia., S44°E, 62.7 ft., with scribing visible.
- A Ponderosa Pine, 17" dia., S50°W, 93.1 ft., with a healed blaze.
- A Ponderosa Pine stump, approx. 1 1/2 ft. dia., N53°W, 5.9 ft. with no marks visible.

Description of monument and accessories established to perpetuate the original location of this corner:

BTs have blaze and a 6" band painted red, BT tags and "Attention" signs. There is a 6' steel fence post with an "Attention" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18°E.

Nov. 2, 1986



Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)


RECEIVED BY
 Umatilla County Surveyor
 Date 12-11-86
 Rec'd By SA
 No. 86-140-M

GPO-788-276

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
(Continued from Page 1 of 2.)
At the corner point they set a
2 1/2" X 28" iron post with a brass cap
marked:
from which:

T6S R32E
S29 | S28
S32 | S33
1968



- A Fir, 8" dia., N67°E, 90 lks.
- A Pine, 16" dia., S50°W, 141 lks.
- A Pine, 10" dia., N60°W, 177 lks.

Description of corner evidence found:

Description of monument and accessories established to perpetuate the original location of this corner:



Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

RECEIVED BY

Umatilla County Surveyor

Date _____

Rec'd By *JA*

No. *86-140-M*

GPO-798-276

Pa 2