

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner, Secs. 28, 29, 32 & 33, T.6S., R.32E., W.M.
 Corner originally set by Frank Campbell under
 Contract No. 468 dated 1883.

His record reads: Set a basalt stone 24"x10"x6" 18 in. 1
 in the ground from which: A Fir, 24" dia., N70°E, 165 1
 lks. A Pine, 24" dia., S44°E, 100 lks. A Pine, 30" 1
 dia., S49°W, 142 lks. A Pine 30" dia., N53°W, 9 lks. 1

In 1968, the BLM remonumented this corner operating 1
 under special instructions dated 1967. They found a 1
 pine 30 ins. diam., S44°E, 95 lks. dist., with healed 1
 blaze and a pine stump, 30 ins. diam., N53°W, 9 lks. 1

dist. From this evidence, they set a standard BLM
 monument marked as shown, from which they set new bearing trees:
 A fir, 8 ins. diam., bears N67°E, 90 lks. dist, mkd. T6SR32ES28BT;
 A pine, 16 ins. diam., bears S50°W, 141 lks. dist. mkd. T6SR32ES32BT;
 A pine, 10" diam., bears N60°W, 177 lks. dist., mkd. T6SR32ES29BT.

Description of corner evidence found:

Found the corner monument as described from which:
 A 34" dbh Ponderosa Pine bears S44°E, 62.7' with visible scribe.
 A 18" dbh Ponderosa Pine stump bears N53°W, 5.9' with no visible marks.
 A 17" dbh Ponderosa Pine bears S48°W, 93.1' with healed blaze.
 A 12" dbh Ponderosa Pine bears N66 1/2°W, 116.8' with healed blaze.
 A dead 12" Douglas Fir bears N67°E, 59.4' with visible scribe.


Description of monument and accessories I established to perpetuate the
 original location of this corner:

Cleared brush and debris from corner and set new bearing tree as
 follows:
 A 8" dbh Douglas Fir bears N60 1/2°E, 75.1' scribed T6SR32ES28BT.
 The bearings are true based on the GPS bearings to the surveyed steel
 post which bears S0 1/2°E, 41.5'.
 An aluminum washer stamped RLS 852 is nailed between the letters B and T.
 on the new tree. All the BT's have LSM and BT signs attached.
 Painted 6" red bands around all the trees and painted the
 scribe blazes red.


This work was done May 25, 1994.

Index: V-9

1	DIAGRAM	1
1	BLM Brass Cap	1
1		1
1	T6S R32E	1
1	S29!S28	1
1	-----	1
1	S32!S33	1
1	1968	1



David L. Haddock



Office of _____ County of _____
 State of _____, I hereby certify that the within instrument was filed
 in this office for record on the _____ day of _____, 19____.

_____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

RECEIVED BY

Umatilla County Surveyor
 Date 7-94
 Rec'd By KK
 No. 94-96-R