


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

Y-6

History of original corner establishment: **BLM ESTABLISHED CORNER**

IN THE DEPENDENT RESURVEY, PORTION OF SUBDIVISIONAL LINES, SUBDIVISION OF SECTION 32, T.6 S., R.32 E., WILLAMETTE MERIDIAN, OREGON IN 1968. SET AN IRON POST, 28 IN. LONG, 2 1/2 IN. DIAM., 10 IN. IN THE GROUND, TO SOLID ROCK, IN A MOUND OF STONE, 3 FT. BASE, TO TOP WITH BRASS CAP MARKED: SW 1/16 S 32 1968



FROM WHICH

- a pine, 14 ins. diam., bears N. 12 1/2° E., 261 lks. dist., mkd. SW 1/16 S 32 BT
- a pine, 30 ins. diam., bears N. 49° W., 236 lks. dist., mkd. SW 1/16 S 32 BT

Description of corner evidence found: 3/4" BLM BRASS CAP MARKED SW 1/16 S 32, SET ON A 2 1/2" IRON POST IN A MOUND OF STONE 1968

FROM WHICH

- A PINE, 34 IN. DIAM. BEARS N. 46° 37' W., 152.50 FT. (RECORD N. 49° W., 236 LKS. OR 155.76 FT) WITH HEADED BLAZE, US FOREST SERVICE SIGN 54-3 ATTACHED
- A PINE, 20 IN. DIAM. BEARS N. 13° 12' E., 171.90 FT. (RECORD N. 12 1/2° E., 261 LKS OR 172.26 FT) WITH HEADED BLAZE, US FOREST SERVICE SIGN 54-3 ATTACHED

Description of monument and accessories I established to perpetuate the

original location of this corner: REPLACED 54-3 SIGN WITH NEW 54-3, ACTUAL BEARING AND DIST. NOTED, ON BEARING TREE : A PINE, 34" DIAM BEARS N/46°37'W., 152.50 FT. ATTACHED US FOREST SERVICE SIGNS 54-9 ON BOTH BT'S! PAINTED RED BAND AROUND BOTH BT'S!

SET STEEL GUARD POST 5 FT. SOUTH OF COR. WITH USFS 54-9 SIGN ATTACHED  
MAGNETIC DECLINATION USED AT THIS CORNER TO EST. BEARINGS: 10°; 19° E.

WITNESS: KEN BATES  
SCOTT KRKA

I HEREBY CERTIFY THE ABOVE CORNER POINT WAS PERPETUATED IN OCT. 1990 AS HEREON STATED.



Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....  
*David A. Klein* by.....  
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

RECEIVED BY  
Umatilla County Surveyor  
Date 3-91  
Rec'd By KA  
No. 91-22-R