


History of original corner establishment:

Original corner established by Frank W. Campbell on July 14, 1883, under contract No. 468 as follows:
Set a post from which:
A 5" Pine bears S20°W, 9 links (5.94 feet).
A 15" Fir bears N40°E, 43 links (28.38 feet).



Description of corner evidence found:

The original post is gone.
A 28" Douglas-fir with double healed blazes bears N40°E, 28.38 feet.

Description of monument and accessories established to perpetuate the original location of this corner:

At record bearing and distance from the original remaining bearing tree, set a 2 1/2" by 30" aluminum pipe 28" into the ground in a small mound of stones. A 3 1/4 inch aluminum cap attached is marked as shown in the diagram above. From which:

A 16" White Fir scribed "1/4 S31 BT" bears N18°W, 27.5 feet.
A 16" White Fir scribed "1/4 S6 BT" bears S55°E, 57.1 feet.
A 29" Douglas-fir scribed "1/4 S6 BT" bears S56°30'W, 48.5 feet.
The northerly high point of a 6 foot by 10 foot by 4 1/2 foot high rock outcrop bears S15°W, 26.7 feet. The rock is not marked.

Each new bearing tree has a 3/4" brass washer, marked "PLS 1636", nailed flush to the lower blaze. All 4 bearing trees have a 54-3, Bearing Tree sign nailed above the blazes and a 54-9, Land Survey Monument sign nailed to the back.

I hereby certify the above corner position was perpetuated as hereon described on September 2, 1993.

Magnetic Declination: 22° E

NAD1983 Geographic Position (+ or - 2 to 6 meters):
Latitude 44-59-51.319 N
Longitude 118-40-02.317 W

Witnessed by: Troy Allen

REGISTERED PROFESSIONAL LAND SURVEYOR
Dennis L. Gaylord
OREGON
JULY 14, 1978
DENNIS L. GAYLORD
1636
EXPIRES 12-31-93

Office of..... County of UMATILLA
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by
(COUNTY OFFICIAL) (DEPUTY)

Umatilla County Surveyor
Date 10-93
Rec'd By KR
No. 93-77-R