

USDA-FOREST SERVICE

Index

File No. C-20

T 7S R. 34 E

Merid. WILLAMETTE

CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)

R.D. NORTH FORK JOHN DAY County Grant


N.F. Umatilla State Oregon

Tract or Survey No. _____

Cor. No. _____

CORNER DIAGRAM

CE 1/16



DESCRIBE CORNER MONUMENT FOUND

None

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

None

PHOTO IDENTIFICATION DATA

Photo No. _____

Filed At. _____

Object Ident. _____

Ident. By _____

Signature

6

PLANE COORDINATE POSITION DATA

State _____ Zone _____

X _____

Y _____

Estab. By _____

Agency

8

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

Take Road 510 off 52 Road to 0.3 miles past posted boundry to CE 1/16 corner which is in open field and can be easily seen from road.

3

Signature

Title

Division

Headquarters

Date

10/25/86

7100-52 (3-68)

Clayton J. Wirth LAND SURVEYOR

4

5

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Set a 2 1/2" DIAM. ALUM. CAP on a 2 1/2" X 30" Alum Pipe w/ Flare on bottom. Cap mkd. per sketch. Set steel posts 4' ± E. & S. w/ Prop. boundry, Attn. and mon. signs attached.

E 1/14
C ——— C
52

RPLS 1910
1986

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

① 8" D.B.H. Lodgepole Pine, N. 18° E., 170.0', scribed CE 1/16 52 BT.

② 7 D.B.H. Lodgepole Pine, N. 72 1/2° W., 40.5', scribed CE 1/16 52 BT.

Each B.T. has a brass washer mkd. RPLS 1910 Btwn. B & T, B.T. tag, Attn. sign and Band f Face Painted Red.

Work Done By C.J. Martin Title Land Surveyor Date 10/25/86 State Registration No. LS 1910
or Agency

Certified Cor. Record Prepared? Yes No Filed At: _____ Date _____

REMARKS

Index File No.
6-20

T. 7 S

R. 34 E

M. WILLAMETTE Tract or Surv. No.

Cor.
CE 1/16