

PLAT AND RECORD OF SURVEY No. 100

Surveyed Mar 21st 1875 jointly by John W. Kimbrell & Geo. A. Wilson
for Nathan Pierce and A. Henson

In T 5 N R 36 E W 4

for the re-establishment of the corner to Secs 4-5-8 & 9 and
the 1/4 sec corners bet said 4 & 9 and 4 & 8

We commenced at the corner to Secs 5-6-7 & 8 which is a stone
firmly set to perpetuate the original corner and is undisputed,
thence east bet Secs 5 & 8

Var $21^{\circ} 30' 6''$

- 6 25 gate Course N 60° W
39 76 U S field Notes set temporary by Sec 4
47 72 as indicated by Notes of J. Bohner on a survey made for
Dr. Blackwell Nov. 25 1876 set temporary 1/4 Sec 4
61 80 gate Course N $20^{\circ} 00'$
67 62 fence Course N & S side road
68 27 a point on the south of the corner which is a stone firmly set
in ground by J. Bohner Nov. 25 1876
68 33 fence course N & S side road into field
77 73 as per U S field Notes set temporary ca for Secs 4-5-8 & 9
88 22 the distance as indicated by Notes of J. Bohner of Nov. 25 1876
set temporary ca for Secs 4-5-8 & 9

thence east bet Secs 4 & 9

- 40 02 cross wire fence Course of fence N & S
70 25 Intersect rail fence course N & S 1/4 S the south of the intersection
of wire fence with rail fence course of wire fence west
Note: The rail fence running north 1/4 mile and south one mile
from this point was built about 1876 or 1877 by Mr. Lewis Holm
(who is present) and a Mr. White, and claim the corner were all
standing bet Secs 8 & 9 and 7 & 10 and has been undisputed for
a period of 16 or 17 years,

We proceed to the 1/4 Sec corner bet Secs 8 & 9 We find the mound
and pits almost obliterated but the old post a cottonwood post
well preserved with small mound of stone to perpetuate corner

Corn.	Degrees	Minutes	Chains	Links
-------	---------	---------	--------	-------

Which from any evidence we could get is undisputed as to location
which also corresponds with Mr. Filds Notes on East side of same
Course NW

Thence we run North bet Sec 8 & 9

N 70 20° 0'

646 Top of low ridge course NW

14 25 gulch course NW

15 15 Top of low ridge course NW

37 46 Intersect over S & W line previously run 14 lks west of
our Temporary State bet for corner to Secs 4-5-8-9 upon
Notes of P. Johnson

40 59 cross old headland in plowed field and woods for
as track line by Sec. Berg, A. Johnson and Nathan Lewis
who also claim this point to be near the original Sec
corner to Secs 4-5-8-9

We make an examination by removing the surface of the
ground for some distance around and at a point 34 lks
East of our line along this headland we find particles
of old charcoal stake about 1/2 inch below the surface
as indicated in Mr. Filds Notes, these particles of charcoal stake
we enclose in small square glass bottle, which we deposit
with one quart of stone coal 2 feet below the surface and
set stone 22x12x10 inches marked with 5 notches on 1 corner
4 notches on East edge, present Nathan Lind Allison
Brdon, C. N. Cross and Sec. Berg, Flynn, A. Johnson
and L. A. Wilson chairman

Thence we run North bet Sec 4 & 5

N 70 20° 52' 0'

40 10 cross new wire fence course S & W

40 62 cross old fence low course S & W

80 62 Intersect North boundary of lot 419 lks East of the

Degrees Minutes Chains Links

- Corner to Sec 4-5-32 833
 then S 30° E bet Sec 4 & 5
- 80 62 to cor to Sec 4-5-889
 then S 0° 27' W bet Sec 8 & 9
 or 20° 32' E
- 40 59 The 1/4 Sec cor bet Sec 8 & 9
 Commencing at the corner to Sec 4-5-889 just
 established we run East bet Sec 4 & 9
 Var 20° 32' E
- 40 15 at point on plowed headland and distance as per Notes
 of P. Zahner we made mark for 1/4 Sec corner by removing
 the surface of earth and about 14 inches below the surface
- 40 12 of the plowed ground we find point of old Cherted Slate
 (as indicated in U.S. Field Notes) which we leave in place
 and undisturbed, we enclose small particles of slate in a
 colored glass bottle which we deposit with one quart of
 Stone Coal 2 feet below the surface 12 inches South of
 old point of slate and set Stone 21+10+7 inches marked
 1/4 on South face and + on top of Stone 12 inches South
 of cherted slate, Resent W. A. Good - C. N. Cross -
 Allison Gordon - Nathan Pierce - and Sen. Berry Hayman
 and A. Haysou and L. A. Wilson as Chasman.
 thence East bet Sec 4 & 9
- 30 16 Soil fence N and S or at
- 70 28 from corner to Sec 4-5-889 an excess of 13 lbs
 over the distance as indicated in Notes of P. Zahner we
 intersect Soil fence N & S
 We then proceed to the corner to Sec 9-10-15-816
 which is the old original corner post somewhat decayed
 but supported in place by mound of Stone at the intersection
 of fences running N-S-E & W from this point which
 corner is also undisputed

Course.	Degrees.	Minutes.	Chains.	Links.

Thence N² W along rail fence

Var 21⁴⁵ S

40 50 Search but found no 1/4th corner

50 00 Search but found no corner to sec 3-4-7810

Thence N³⁰ 35' S bet sec 3 8 4

Var 20' S

83 19 Intersect North boundary at Cor^y sec 3-4-33 934

Thence S³⁰ 30' W on true line

82 92 the proportional distance as per notes of S. Zahner on survey Nov. 28 1876 we set stone 24 x 4 x 4 inches for cor to sec 3-4-7810

Thence N⁸⁷ 25' W on true line bet sec 4 8 7

Var 21⁰⁵ S

30 16 the 1/4th cor bet sec 4 8 9 just reestablished

70 28 the corner to sec 4-5-889 just reestablished

Thence west bet sec 5 8 8

Var 20' 32' S

20 21 Intersect 1/4th corner on subdivision pt by S. Zahner

Nov 28 1876

40 43 the distances as given in notes of S. Zahner also locality as pointed out by Sen. Berry Nathan Pierce and A. H. Brown we find by removing the surface of ground, pieces of charred slate about 20 inches below the surface in earth which has not been disturbed for many years. We enclose particles of charred wood part of the extensive slate found by L. A. Wilson at this same point Nov. 17 1892 while searching for this corner in glass fruit jar. which we deposit 2 feet below the surface with one quart of mineral oil bet stone 26 x 13 x 4 inches marked 1/4 on south face for 1/4th corner bet sec 5 8 8. Presons - Allison, Gordon and Nathan Pierce, and Sen. Berry Haysman

